

TOUGH. DURABLE. BUILT TO LAST.

TITAN MOVES THE WORLD™



1.800.USA.BEAR | www.titan-intl.com

Tire Databook Volume 14

Titan Agricultural, Earthmoving/Construction and Consumer Tires

Contents

Radial R-1/R-1S	2	FI.....	19
Titan Hi Traction Lug Radial R-1.....	2	Titan Highway Implement FI.....	19
Titan Hi Power Lug Radial R-1	3	Smooth	19
Titan Super Hi-Power Lug II Radial R-1	3	Titan Road Roller/Road Roller II.....	19
Titan Hi Load Radial R-1S	3	HF-1, HF-2	20
Bias R-1	4	Titan Soft Turf/LSW and LSW 430 HF-1	20
Titan Hi Traction Lug R-1	4	Titan Flo-Trac Rib HF-1	20
Titan Hi Power Lug R-1	6	Titan Multi Trac C/S HF-1	20
Titan Tru Power R-1	7	Titan Classic Rib HF-1	20
Titan Farm Tractor R-1	7	Titan Classic TX HF-1	20
Titan Irrigation Drive R-1	7	Titan Flo-Trac Lug HF-2.....	20
Titan Traction Drive R-1	7	Titan Tru Power II HF-2	20
Titan Lift Rigger II R-1.....	8	Bias Skid Steer.....	22
Titan TT415 R-1	8	Titan Contractor FWD SS	22
Radial R-1W	9	Titan H/E SS	22
Titan AG49V Radial R-1W.....	9	Titan HD2000 SS.....	22
Titan AG49H Radial R-1W.....	9	Titan HD2000 II SS.....	22
Titan AG49M Radial R-1W.....	9	Titan Trac Loader SS.....	22
Titan Grizz LSW AG49H Radial R-1W.....	10	Titan Trac Loader Chevron SS.....	22
Titan Grizz LSW AG49M Radial R-1W.....	10	ATV.....	24
Bias R-2	11	Titan 489 X/T Rears ATV	24
Titan Special Service R-2.....	11	Titan 589 M/T Rears ATV	24
Radial R-3.....	11	Titan Fast Trekker Rears ATV	25
Titan Torc Trac Radial R-3.....	11	Titan Sabre Tooth ATV.....	25
Titan Torc Trac II Radial R-3.....	11	Titan Mud Monster ATV.....	25
Bias R-3, R-4.....	12	Titan Raptor ATV.....	25
Titan Torc Trac R-3.....	12	ST.....	26
Titan Torc Trac II R-3.....	12	Dico ST Radial	26
Titan Grizz LSWG9F R-4.....	12	Dico ST Radial II	26
Titan Industrial Tractor Lug R-4.....	13	Titan ST	26
Titan Industrial Contractor R-4	13	Titan Sport Trax ST	26
Titan Industrial Tractor Lug II R-4.....	13		
Bias F-1, F-2, F-2M, F-3	14		
Titan Tru-Trac Front Tractor F-1	14		
Titan Tru-Trac F-2	14		
Titan Tru-Trac Multi Rib F-2M	14		
Titan Contractor F-3	15		
Titan Industrial Front Tractor F-3.....	15		
Bias I-1, I-3	16		
Titan Dura Life I-1	16		
Titan Hi Flotation I-1.....	16		
Titan Packer I-1	16		
Titan Planter AG41B I-1	16		
Titan Grizz LSW 410/411 I-1	17		
Titan Grizz LSW G2E I-3.....	18		
Titan Contractor I-3	18		
Titan Contractor II I-3	18		
Titan TI422 I-3	18		
Titan Traction Implement I-3.....	18		
		Middle of the Book	
		Tire Information Section.....	1-70
		Industry Standards/Tire Selection Chart.....	1
		Radial Sizes by Rolling Circumference	2
		Int'l Load Index/Speed Symbols.....	3
		Rolling Circumference	4
		Optimum Tractor Tire Performance	5
		LSW & Metric Conversion Tables	9
		Load & Inflation Tables.....	10
		Horse Power Capability	51
		Liquid Fill Procedures.....	56
		Approved Rim Contours	62
		RCI Chart.....	70
		Safety Section	S:1-22

Titan**Radial R-1**

Titan Hi Traction Lug Radial R-1

- Superior traction and side hill slip resistance
- Combines long bar/medium bar traction for cleanability, smooth ride and more power to the ground

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
4RD414	12.4R24	Hi Traction Lug	TL	122A8/B	36	30	3,300	11	13.3	46.1	20.9	138	120	126	44
4RDH14	320/85R24	Hi Traction Lug	TL	142A8/B	67	30	5,840	13	15.4	50.4	22.7	150	206	139	47
4RD412	12.4R28	Hi Traction Lug	TL	121A8/B	30	30	3,200	11	12.7	49.6	22.5	149	120	136	44
4RD422	13.6R24	Hi Traction Lug	TL	128A8/B	24	30	3,960	12	14.3	48.3	21.7	145	146E	146	46
48E324	13.6R28	Hi Traction Lug	TL	3*	30	30	3,740	12	14.2	52.5	23.7	156	156E	195	51
4RD434	14.9R24	Hi Traction Lug	TL	120A8/B	18	30	3,080	13	17	49.9	23.2	149	150E	161	47
48E438	380/85R28	Hi Traction Lug	TL	133A8/B	23	30	4,540	13	16	54.2	24.9	162	160E	205	50
48E430	380/85R30	Hi Traction Lug	TL	135A8/B	23	30	4,800	13	16	56.2	25.6	169	165E	222	50
48E435	380/85R34	Hi Traction Lug	TL	137A8/B	23	30	5,080	13	16	60.2	27.6	181	224	234	52
48E79A	380/85R34	Hi Traction Lug	TL	148A8/B	46	30	6,950	13	16	60.2	27.6	181	224	254	52
48EA32	380/90R46	Hi Traction Lug	TL	144A8/B	23	30	6,150	13	15.7	72.3	34	218	300	322	50
48ED32	380/90R46	Hi Traction Lug	TL	149A8/B	35	30	7,150	13	15.7	72.3	34	218	300	322	50
48EH32	380/90R46	Hi Traction Lug	TL	156A8/B	49	30	8,800	13	15.7	72.3	34	218	300	355	50
48E032	380/90R46	Hi Traction Lug	TL	168A8/B	78	30	12,300	13	15.7	72.3	34	218	300	368	50
48E246	16.9R26	Hi Traction Lug	TL	2*	24	30	4,800	15	18.1	54.4	24.5	163	196E	222	52
48E220	16.9R38	Hi Traction Lug	TL	2*	24	30	5,680	15	18	66.6	30.6	200	235E	298	52
48E448	420/85R28	Hi Traction Lug	TL	139A8/B	23	30	5,360	15	18.1	56.5	25.5	169	202E	259	52
48E479	420/90R30	Hi Traction Lug	TL	142A8/B	23	30	5,840	15	17.8	58.9	26.7	176	208E	256	56
48E256	18.4R26	Hi Traction Lug	TL	2*	24	30	5,520	16	19.4	57.1	25.1	170	246E	286	53
48E456	18.4R26	Hi Traction Lug	TL	150A8/B	38	30	7,850	16	19.4	57.1	25.1	170	262E	310	53
4RD450	18.4R30	Hi Traction Lug	TL	143A8/B	24	30	6,000	16	19.4	61.7	28.2	183	255E	254	50
48E154	18.4R34	Hi Traction Lug	TL	1*	18	30	5,360	16	18.8	65.1	29.6	195	356	322	53
48E477	480/80R38	Hi Traction Lug	TL	149A8/B	23	30	7,150	16	19.8	69.1	31.6	208	454	356	53
48E677	480/80R38	Hi Traction Lug	TL	152A8/B	29	30	7,850	16	19.8	69.1	31.6	208	454	369	53
48E442	480/80R42	Hi Traction Lug	TL	151A8/B	23	30	7,600	16	19.3	73.1	33.6	220	400E	394	53
48E542	480/80R42	Hi Traction Lug	TL	154A8/B	29	30	8,250	16	19.3	73.1	33.6	220	400E	394	53
48E842	480/80R42	Hi Traction Lug	TL	162A8/B	46	30	10,500	16	19.3	73.1	33.6	220	400E	421	53
48E942	480/80R42	Hi Traction Lug	TL	166A8/B	58	30	11,700	16	19.3	73.1	33.6	220	400E	429	53
48E447	480/80R46	Hi Traction Lug	TL	155A8/B	29	30	8,550	16	19.3	78.9	35.9	235	425E	409	53
48E547	480/80R46	Hi Traction Lug	TL	158A8/B	35	30	9,350	16	19.3	78.9	35.9	235	425E	414	53
48E489	520/85R38	Hi Traction Lug	TL	148A8/B	17	30	6,950	18	21.3	72.9	33.1	218	430E	421	55
48E689	520/85R38	Hi Traction Lug	TL	158A8/B	29	30	9,350	18	21.3	72.9	33.1	218	430E	455	55
48E452	520/85R42	Hi Traction Lug	TL	157A8/B	23	30	9,100	18	21.3	76.9	35.1	231	435E	516	55
48E199	24.5R32	Hi Traction Lug	TL	1*	18	30	8,520	21	25.3	70.6	31.6	211	461E	513	56
48E599	24.5R32	Hi Traction Lug	TL	5*	38	30	12,800	21	25.3	70.6	31.6	211	461E	596	56

*See Approved Rim Contours section

Radial R-1/R-1S

Titan



Titan Hi Power Lug Radial R-1

- Single Bar Design with wide overlapping lugs
- Deep Tread and excellent tread wear and durability
- Designed to deliver power to the ground
- Design offers maximum cleaning and sidehill slip resistance

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
4R3434	14.9R24	Hi Power Lug	TL	120A8/B	18	30	3,080	13	15.5	49.8	22.7	148	155E	161	47
4R3450	18.4R30	Hi Power Lug	TL	143A8/B	24	30	6,000	16	19.3	61	27.3	182	268E	254	50
4R3750	480/80R30	Hi Power Lug	TL	139A8/B	17	30	5,360	16	19.2	60.5	27.1	181	347	254	50
49T454	480/80R34	Hi Power Lug	TL	140A8/B	17	30	5,520	16	19.5	64.5	28.9	193	429	334	54
49T252	20.8R42	Hi Power Lug	TL	155A8/B	24	30	8,550	18	21.2	76.5	35	230	400E	485	55
4R36Q7	23.1R30	Hi Power Lug	TL	168A8	46	30	12,300	20	24	66.5	30.1	200	350E	483	52

*See Approved Rim Contours section



Titan Super Hi-Power Lug II Radial R-1

- Single bar design with wide overlapping lugs
- Deep tread cuts through soil and penetrates easily for maximum traction
- Also provides excellent tread wear and durability

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
48T596	800/65R32	Super Hi-Power Lug II	TL	172A8/B	35	30	13,900	27	31.1	71.9	32.3	214	na	747	59

*See Approved Rim Contours section



Titan Hi Load Radial R-1S

- Delivers superior tread wear
- Reduced lug-induced vibration
- Higher load capabilities over standard R-1 radials
- Stability at transport speeds

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
48S532	380/90R46	Hi Load Radial	TL	154A8/B	42	30	8,250	13	15.7	72.3	34	218	234	352	41
48S832	380/90R46	Hi Load Radial	TL	164A8/B	68	30	11,200	13	15.7	72.3	34	218	234	390	41
48S032	380/90R46	Hi Load Radial	TL	168A8/B	78	30	12,300	13	15.7	72.3	34	218	234	403	41

*See Approved Rim Contours section

Titan**Bias R-1**

Titan Hi Traction Lug R-1

- Exclusive long bar/medium bar tread pattern
- This design follows a symmetrical lug pattern to eliminate side-to-side rocking and promotes even wear

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
48D665	7-14	Hi Traction Lug	TL	6	36	20	990	6	6.7	27.5	12.7	83	66	26	33
48D666	7-16	Hi Traction Lug	TL	6	36	20	1,100	6	7.3	29.3	13.4	87	68E	27	34
48D667	8-16	Hi Traction Lug	TL	6	28	20	1,360	6	8	30.5	13.9	91	72E	37	31
48D684	8.3-24	Hi Traction Lug	TL	6	34	20	1,610	7	8.3	39.1	18.2	117	60E	56	37
48D695	9.5-16	Hi Traction Lug	TL	6	30	20	1,390	8	9.5	33.3	15	100	55E	48	40
48D663	9.5-20	Hi Traction Lug	TL	6	30	20	1,650	8	9.2	37.7	17.2	113	64E	54	41
48D694	9.5-24	Hi Traction Lug	TL	6	30	25	1,870	8	9.5	41.2	19	123	73E	66	30
48D404	11.2-24	Hi Traction Lug	TL	4	18	25	1,650	10	11.8	43.6	20.1	130	99	95	43
48D604	11.2-24	Hi Traction Lug	TL	6	26	25	2,090	10	11.8	43.6	20.1	130	99	98	43
47D804	11.2-24	Hi Traction Lug	TT	4	18	25	1,650	10	11.8	43.6	20.1	130	99	91	43
48D804	11.2-24	Hi Traction Lug	TL	8	36	25	2,540	10	11.8	43.6	20.1	130	99	99	43
48D004	11.2-24	Hi Traction Lug	TL	10	44	25	2,830	10	11.8	43.6	20.1	130	99	102	43
48D410	11.2-28	Hi Traction Lug	TL	4	18	25	1,760	10	11.8	47.6	22.1	147	100E	100	43
48D414	12.4-24	Hi Traction Lug	TL	4	16	25	1,870	11	12.3	46.7	21	141	147E	106	44
48D614	12.4-24	Hi Traction Lug	TL	6	24	25	2,400	11	12.3	46.7	21	141	147E	111	44
48D814	12.4-24	Hi Traction Lug	TL	8	32	25	2,830	11	12.3	46.7	21	141	147E	111	44
48D114	12.4-24	Hi Traction Lug	TL	12	48	25	3,520	11	12.3	46.7	21	141	147E	128	44
48D612	12.4-28	Hi Traction Lug	TL	6	24	25	2,540	11	13	49.8	23.1	152	150E	113	44
47D619	12.4-42	Hi Traction Lug	TT	6	24	25	3,080	11	12.5	64.5	30.3	193	155E	157	32
48D019	12.4-42	Hi Traction Lug	TL	10	40	25	4,180	11	12.5	64.5	30.3	193	155E	180	48
48D119	12.4-42	Hi Traction Lug	TL	12	48	25	4,680	11	12.5	64.5	30.3	193	155E	181	48
48D422	13.6-24	Hi Traction Lug	TL	4	14	25	2,040	12	14.3	47.9	21.9	143	143E	128	46
48D622	13.6-24	Hi Traction Lug	TL	6	22	25	2,680	12	14.3	47.9	21.9	143	143E	129	46
48D822	13.6-24	Hi Traction Lug	TL	8	28	25	3,080	12	14.3	47.9	21.9	143	143E	137	46
47D424	13.6-28	Hi Traction Lug	TT	4	14	25	2,200	12	14.3	51.9	23.9	158	156E	126	46
48D424	13.6-28	Hi Traction Lug	TL	4	14	25	2,200	12	14.3	51.9	23.9	158	156E	134	46
47D624	13.6-28	Hi Traction Lug	TT	6	22	25	2,830	12	14.3	51.9	23.9	158	156E	133	46
48D624	13.6-28	Hi Traction Lug	TL	6	22	25	2,830	12	14.3	51.9	23.9	158	156E	141	46
48D024	13.6-28	Hi Traction Lug	TL	10	36	25	3,740	12	14.3	51.9	23.9	158	156E	146	46
48D434	14.9-24	Hi Traction Lug	TL	4	12	25	2,200	13	15.4	50.4	22.7	150	150E	118	47
47D634	14.9-24	Hi Traction Lug	TT	6	20	25	3,000	13	15.4	50.4	22.7	150	150E	130	47
48D634	14.9-24	Hi Traction Lug	TL	6	20	25	3,000	13	15.4	50.4	22.7	150	150E	140	47
48D834	14.9-24	Hi Traction Lug	TL	8	26	25	3,520	13	15.4	50.4	22.7	150	150E	141	47
47D638	14.9-28	Hi Traction Lug	TT	6	20	25	3,200	13	15.7	54.1	24.8	163	163E	132	47
48D638	14.9-28	Hi Traction Lug	TL	6	20	25	3,200	13	15.7	54.1	24.8	163	163E	138	47
48D038	14.9-28	Hi Traction Lug	TL	10	32	25	4,180	13	15.7	54.1	24.8	163	163E	161	47
48D030	14.9-30	Hi Traction Lug	TL	10	32	25	4,300	13	15.7	56.1	25.8	169	168E	189	47
47D674	15.5-38	Hi Traction Lug	TT	6	20	25	3,520	14	15.9	62.7	29.3	189	175E	183	46
47D874	15.5-38	Hi Traction Lug	TT	8	26	25	4,080	14	15.9	62.7	29.3	189	175E	185	46
47D645	16.9-24	Hi Traction Lug	TT	6	18	25	3,420	15	17.8	53	24	157	190E	147	48
48D645	16.9-24	Hi Traction Lug	TL	6	18	25	3,420	15	17.8	53	24	157	190E	160	48

Bias R-1

Titan

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
48D845	16.9-24	Hi Traction Lug	TL	8	24	25	4,080	15	17.8	53	24	157	190E	160	48
48D646	16.9-26	Hi Traction Lug	TL	6	18	25	3,520	15	17.7	55	25	164	196E	166	48
48D046	16.9-26	Hi Traction Lug	TL	10	28	25	4,540	15	17.7	55	25	164	196E	183	48
48D648	16.9-28	Hi Traction Lug	TL	6	18	25	3,640	15	17.8	57	26	170	202E	175	48
47D848	16.9-28	Hi Traction Lug	TT	8	24	25	4,300	15	17.8	57	26	170	202E	168	48
48D048	16.9-28	Hi Traction Lug	TL	10	28	25	4,680	15	17.8	57	26	170	202E	192	48
47D679	16.9-30	Hi Traction Lug	TT	6	18	25	3,740	15	17.8	59	27	176	209E	175	48
48D679	16.9-30	Hi Traction Lug	TL	6	18	25	3,740	15	17.8	59	27	176	209E	186	48
47D879	16.9-30	Hi Traction Lug	TT	8	24	25	4,400	15	17.8	59	27	176	209E	179	48
47D644	16.9-34	Hi Traction Lug	TT	6	18	25	4,680	15	17.8	63	29	188	222E	189	48
47D844	16.9-34	Hi Traction Lug	TT	8	24	25	4,680	15	17.8	63	29	188	222E	190	48
47D620	16.9-38	Hi Traction Lug	TT	6	18	25	4,180	15	17.8	67	31	200	235E	198	48
47D820	16.9-38	Hi Traction Lug	TT	8	24	25	4,940	15	17.8	67	31	200	235E	206	48
48D890	18.4-16.1	Hi Traction Lug	TL	8	20	25	2,910	16	18.6	44.7	20.9	135	158E	166	50
48D656	18.4-26	Hi Traction Lug	TL	6	16	25	3,960	16	19.4	57.7	26.2	171	246E	192	50
48D056	18.4-26	Hi Traction Lug	TL	10	26	25	5,200	16	19.4	57.7	26.2	171	246E	210	50
48D156	18.4-26	Hi Traction Lug	TL	12	32	25	5,840	16	19.4	57.7	26.2	171	246E	217	50
48D650	18.4-30	Hi Traction Lug	TL	6	16	25	4,180	16	19.4	61.7	28.2	183	263E	228	50
47D850	18.4-30	Hi Traction Lug	TT	8	20	25	4,800	16	19.4	61.7	28.2	183	263E	208	50
48D050	18.4-30	Hi Traction Lug	TT	10	26	25	5,520	16	19.4	61.7	28.2	183	263E	256	50
47D654	18.4-34	Hi Traction Lug	TT	6	16	25	4,400	16	19.4	65.7	30.2	195	279E	213	50
47D854	18.4-34	Hi Traction Lug	TT	8	20	25	5,080	16	19.4	65.7	30.2	195	279E	219	50
48D054	18.4-34	Hi Traction Lug	TL	10	26	25	6,000	16	19.4	65.7	30.2	195	279E	262	50
47D677	18.4-38	Hi Traction Lug	TT	6	16	25	4,680	16	19.4	69.7	32.2	206	295E	246	50
47D877	18.4-38	Hi Traction Lug	TT	8	20	25	5,360	16	19.4	69.7	32.2	206	295E	251	50
47D077	18.4-38	Hi Traction Lug	TT	10	26	25	6,400	16	19.4	69.7	32.2	206	295E	277	50
48D377	18.4-38	Hi Traction Lug	TL	14	36	25	7,600	16	19.4	69.7	32.2	206	295E	376	50
47D801	20.8-34	Hi Traction Lug	TT	8	18	25	5,840	18	21.7	68.9	31.5	203	322E	277	51
47D889	20.8-38	Hi Traction Lug	TT	8	18	25	6,150	18	21.7	72.9	33.5	214	341E	314	51
47D089	20.8-38	Hi Traction Lug	TT	10	22	25	6,950	18	21.7	72.9	33.5	214	341E	312	51
47D389	20.8-38	Hi Traction Lug	TT	14	32	25	8,550	18	21.7	72.9	33.5	214	341E	414	51
48DD89	20.8-38	Hi Traction Lug	TL	28	62	25	12,800	18	21.7	72.9	33.5	214	341E	449	51
48D886	23.1-26	Hi Traction Lug	TL	8	16	25	5,680	20	24.1	64.3	28.9	187	322E	308	52
48D086	23.1-26	Hi Traction Lug	TL	10	20	25	6,400	20	24.1	64.3	28.9	187	322E	331	52
48D186	23.1-26	Hi Traction Lug	TL	12	24	25	7,150	20	24.1	64.3	28.9	187	322E	340	52
48D586	23.1-26	Hi Traction Lug	TL	16	34	25	8,800	20	19.4	57.7	26.2	171	322E	339	52
47D888	23.1-34	Hi Traction Lug	TT	8	16	25	6,400	20	24.1	72.3	32.9	211	364E	300	52
48D099	24.5-32	Hi Traction Lug	TL	10	20	25	7,850	21	25.5	72.2	32.7	210	364E	393	53
48D199	24.5-32	Hi Traction Lug	TL	12	24	25	8,800	21	25.5	72.2	32.7	210	364E	437	53
48D399	24.5-32	Hi Traction Lug	TL	14	28	25	9,650	21	25.5	72.2	32.7	210	364E	438	53
48DBQ8	24.5-32	Hi Traction Lug	TL	24	46	25	12,800	21	25.5	72.2	32.7	210	364E	479	53
48D196	30.5L-32	Hi Traction Lug	TL	12	20	25	9,350	27	31.9	71.8	32.5	209	468E	544	54
48D596	30.5L-32	Hi Traction Lug	TL	16	26	25	11,000	27	31.9	71.8	32.5	209	468E	578	54

*See Approved Rim Contours section

Titan**Bias R-1**

Titan Hi Power Lug R-1

- Single Bar Design with wide overlapping lugs
- Deep Tread and excellent tread wear and durability
- Designed to deliver power to the ground
- Design offers maximum cleaning and sidehill slip resistance

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
473404	11.2-24	Hi Power	TT	4	18	25	1,650	10	11.6	43.5	20.1	130	99	81	42
483404	11.2-24	Hi Power	TL	4	18	25	1,650	10	11.6	43.5	20.1	130	99	95	42
473408	11.2-38	Hi Power	TT	4	18	25	2,090	10	11.6	57.5	27.1	174	115E	113	42
483408	11.2-38	Hi Power	TL	4	18	25	2,090	10	11.6	57.5	27.1	174	115E	122	42
473418	12.4-38	Hi Power	TT	4	16	25	2,340	11	12.9	59.6	28	181	145E	140	44
483818	12.4-38	Hi Power	TL	8	32	25	3,520	11	12.9	59.6	28	181	145E	160	44
483118	12.4-38	Hi Power	TL	12	48	25	4,400	11	12.9	59.6	28	181	145E	177	44
473624	13.6-28	Hi Power	TT	6	22	25	2,830	12	14.1	51.6	23.7	157	156E	127	46
473628	13.6-38	Hi Power	TT	6	22	25	3,300	12	14.1	61.6	28.8	186	181E	154	46
483128	13.6-38	Hi Power	TL	12	42	25	4,800	12	14.1	61.6	28.8	186	181E	216	46
473434	14.9-24	Hi Power	TT	4	12	25	2,200	13	15.5	49.8	22.7	148	150E	104	47
483434	14.9-24	Hi Power	TL	4	12	25	2,200	13	15.5	49.8	22.7	148	150E	118	47
473634	14.9-24	Hi Power	TT	6	20	25	3,000	13	15.5	49.8	22.7	148	150E	129	47
483634	14.9-24	Hi Power	TL	6	20	25	3,000	13	15.5	49.8	22.7	148	150E	139	47
473631	14.9-26	Hi Power	TT	6	20	25	3,080	13	15.1	51.8	23	156	155E	151	47
483031	14.9-26	Hi Power	TT	10	32	25	4,080	13	15.1	51.8	23	156	155E	182	47
483131	14.9-26	Hi Power	TL	12	36	25	4,400	13	15.1	51.8	23	156	155E	189	47
483638	14.9-28	Hi Power	TL	6	26	25	3,200	13	15.2	54.9	24.6	164	160E	138	47
483038	14.9-28	Hi Power	TL	10	32	25	4,180	13	15.2	54.9	24.6	164	160E	161	47
473673	14.9-38	Hi Power	TT	6	32	25	4,300	13	15.1	63.8	29.7	192	170E	190	47
473679	16.9-30	Hi Power	TT	6	18	25	3,740	15	17.6	58.5	26.8	175	209E	175	48
473658	18.4-28	Hi Power	TT	6	16	25	4,080	16	19.1	59.1	26.9	175	250E	182	50
473650	18.4-30	Hi Power	TT	6	16	25	4,180	16	19.1	61.1	27.9	181	263E	203	50
473654	18.4-34	Hi Power	TT	6	16	25	4,400	16	19.1	65.1	29.9	193	279E	213	50
473677	18.4-38	Hi Power	TT	6	16	25	4,680	16	19.1	69.1	31.9	205	295E	246	50
473877	18.4-38	Hi Power	TT	8	20	25	5,360	16	19.1	69.1	31.9	205	295E	251	50
473889	20.8-38	Hi Power	TT	8	18	25	6,150	18	21.6	72.2	33.2	213	341E	304	51
483086	23.1-26	Hi Power	TL	10	20	25	6,400	20	24	62.5	28.1	183	322E	341	52
473882	23.1-30	Hi Power	TT	8	16	25	6,000	20	24	66.5	30.1	195	340E	324	52
483082	23.1-30	Hi Power	TL	10	20	25	6,800	20	24	66.5	30.1	195	340E	360	52
48Q196	30.5L-32	Hi Power	TL	12	26	25	9,350	27	31.1	71.5	31.9	213	468E	568	59

*See Approved Rim Contours section

Bias R-1

Titan



Titan Tru Power R-1

- Ultimate deep-traction tire with a large contact area to provide the best traction
- A great performer on wet or dry surfaces
- Features a specially designed rim guard to keep debris from the bead seat area

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
4233F5	5-12	Tru Power	TL	4	34	10	495	4	5	20.8	9.6	62	na	11	20
4233C3	6-12	Tru Power	TL	4	28	10	600	5	5.7	22.7	10.3	70	na	14	20
423382	7-12	Tru Power	TL	4	24	10	715	6	6.5	23.9	10.9	72	na	18	23
423383	12.4-16	Tru Power	TL	6	24	10	1,820	11	12.4	37.7	17.2	112	na	69	32

*See Approved Rim Contours section



Titan Farm Tractor R-1

- Great size range for antique and older tractors
- The open 45 degree lug provides self-cleaning and traction benefits

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
470402	11.2-34	Farm Tractor	TT	4	18	25	1,980	10	11.6	53.4	25.1	164	na	97	42
470406	11.2-36	Farm Tractor	TT	4	18	25	2,040	10	11.2	55.4	26.1	170	na	93	44
470416	12.4-36	Farm Tractor	TT	4	16	25	2,270	11	12.6	57.1	26.4	171	na	115	44
470616	12.4-36	Farm Tractor	TT	6	24	25	2,830	11	12.6	57.1	26.4	171	na	129	44
470693	13.9-36	Farm Tractor	TT	6	20	25	3,200	12	14.2	58.7	27.4	178	na	131	44

*See Approved Rim Contours section



Titan Irrigation Drive R-1

- Designed for irrigation service with minimal soil compaction and excellent wear



Titan Traction Drive R-1

- Titan's Irrigation Drive and Traction Drive R-1 tires are designed for irrigation service with minimal soil compaction and excellent wear

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
499434	14.9-24	Irrigation Drive	TL	4	16	25	4,640	13	15.5	49.8	22.7	148	150E	128	47
499634	14.9-24	Irrigation Drive	TL	6	26	25	6,330	13	15.5	49.8	22.7	148	150E	129	47
499511	14.9-24	Traction Drive	TL	4	16	25	4,640	13	15.4	50	22.8	149	150E	110	47

*See Approved Rim Contours section

Titan

Bias R-1



Titan Lift Rigger II R-1

- Combines thicker, self-cleaning lugs in a directional pattern with a low aspect ratio
- Greater lateral stability and flotation than conventional aerial lift tires
- Also available in the stable LSW design

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
43C103	17.5L-24	Lift Rigger II	TL	12	36	25	6,600	15	17.5	49.8	22.8	149	na	218	49
G3C34L	LSW400-648	Lift Rigger II	TL	166A2	58	25	7,150	356	15.7	42.9	19.3	127	na	152	33
43C34L	400/70-20	Lift Rigger II	TL	150A8/B	61	25	7,400	14	15.9	42.9	19.3	127	na	163	33

*See Approved Rim Contours section



Titan TT415 R-1

- Combine tire features increased contact area for increased flotation
- Turf- and soil-friendly tread pattern

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
4151F3	19.5L/60-26	TT415	TL	12	48	25	9,490	16	19.7	49.6	21.4	146	na	212	42
4151C7	23.5/55-26	TT415	TL	12	40	25	11,540	20	23.6	53.1	22.4	156	na	321	49
45R1C7	23.5/55-26	TT415	TL	168A8/B	40	25	11,700	20	23.6	53.1	22.4	156	na	315	49

*See Approved Rim Contours section

Radial R-1W

Titan



Titan AG49V Radial R-1W

- Developed for high clearance with the Row Crop market in mind and features a deeper tread than an R-1 tire for improved traction



Titan AG49H Radial R-1W

- Modeled after popular European-style tires
- Specifically designed for soft, moist and sticky soils
- Deep tread for solid traction



Titan AG49M Radial R-1W

- Wide base and wider section width allow for higher loads
- Greater flotation, improved traction and smoother ride

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
49V4V4	230/95R48	AG49V	TL	147A8/B	73	30	6,800	8	9.5	67.1	31.7	206	174	203	56
49V7T3	230/115R54	AG49V	TL	146A8/B	64	30	6,600	8	10.5	76.7	36	238	142	312	58
49V5V4	250/95R48	AG49V	TL	147A8/B	73	30	6,800	8	9.5	67.1	31.7	206	174	203	56
49V7V1	290/90R38	AG49V	TL	138A8/B	46	30	5,200	9	11.4	58.5	27.3	184	153E	187	54
49V7V2	320/80R42	AG49V	TL	130A8/B	23	30	4,180	10	12.5	62.2	29.2	191	177E	223	60
49V445	320/85R38	AG49V	TL	138A8/B	41	30	5,200	10	12.6	59.4	27.3	179	162E	220	55
49V7V8	320/90R46	AG49V	TL	148A8/B	52	30	6,950	10	12.6	68.7	32.2	210	216	267	54
49V7T5	320/90R46	AG49V	TL	156A8/B	70	30	8,800	10	12.6	68.7	32.2	210	216	311	54
49V4V6	320/90R50	AG49V	TL	156A8/B	78	30	8,800	10	12.5	72.6	34.2	220	170	327	54
49V8V6	320/90R50	AG49V	TL	161A8/B	78	30	10,200	10	12.5	72.6	34.2	220	170	340	54
49V743	320/90R54	AG49V	TL	154A8/B	60	30	8,250	10	12.5	76.7	35.2	233	178	330	56
49V7V9	380/90R54	AG49V	TL	152A8/B	35	30	7,850	12	15	80.9	37.9	244	178	378	58
49M7M3	380/80R38	AG49M	TL	142A8/B	35	30	5,840	12	15	61.9	28.7	186	246	247	60
49H748	16.9R28	AG49H	TL	136A8/B	24	30	4,940	15	16.8	56	25.7	166	228E	249	63
49H479	16.9R30	AG49H	TL	144A8/B	36	30	6,150	15	17.5	57.7	26.5	175	233E	264	60
49M7M4	420/85R34	AG49M	TL	147A8/B	35	30	6,800	15	16.5	62.1	28.4	188	243	276	56
49M440	480/70R30	AG49M	TL	152A8/B	46	30	7,850	15	18.4	57.8	26.2	171	264E	299	66
49M7M5	480/70R34	AG49M	TL	155A8/B	46	30	8,550	15	18.3	62.2	28.4	189	300	319	62
49H777	18.4R38	AG49H	TL	146A8/B	24	30	6,600	16	18.5	68	31.1	203	318E	350	66
49H742	18.4R42	AG49H	TL	148A8/B	24	30	6,950	16	18.3	72.2	33.2	212	335E	441	66
49M751	480/80R50	AG49M	TL	159A8/B	35	30	9,650	15	18.9	80.2	37.2	245	432	527	64
49H789	20.8R38	AG49H	TL	153A8/B	24	30	8,050	18	20.9	70.9	32.6	212	380E	462	70
49H752	20.8R42	AG49H	TL	155A8/B	24	30	8,550	18	21.4	75.5	34.1	225	423	498	66
49M771	520/85R46	AG49M	TL	158A8/B	23	30	9,350	16	21.9	80.8	37	243	580	568	72
49M5Q5	600/60R34	AG49M	TL	164A8/B	46	30	11,000	18	23.2	63.2	28.2	189	na	495	65
49M765	600/65R28	AG49M	TL	147A8/B	23	30	6,800	18	22.6	58.6	26.4	175	325E	353	69
49M7M6	600/70R30	AG49M	TL	152A8/B	23	30	7,850	20	22.9	63.1	28.4	189	357E	375	65
49M5M6	600/70R30	AG49M	TL	165A8/B	46	30	11,400	20	22.9	63.1	28.4	189	357E	417	65

Titan

Radial R-1W

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
49M770	620/70R42	AG49M	TL	160A8/B	23	30	9,900	20	24.6	76.5	35	230	465E	640	66
49M781	620/70R46	AG49M	TL	162A8/B	23	30	10,500	20	24.6	80.2	36.9	241	470	685	73
49M769	710/70R38	AG49M	TL	166A8/B	23	30	11,700	23	28	76	34.8	227	490E	644	78
49M791	710/70R42	AG49M	TL	168A8/B	23	30	12,300	23	28.2	81.1	36.8	245	572E	748	74
49M891	710/70R42	AG49M	TL	179A8/B	46	30	17,100	23	28.2	81.1	36.8	245	572E	832	74
49M5Q6	710/70R42	AG49M	TL	180A8/B	49	30	17,600	23	28	76	34.8	227	572E	797	78

*See Approved Rim Contours section



Titan Grizz LSW AG49H Radial R-1W

- Patented wheel and tire assembly designed to reduce vehicle bounce, loping and power hop
- Features low aspect ratio tire and a large diameter wheel for greater lateral stability



Titan Grizz LSW AG49M Radial R-1W

- Largest drive wheel radial tire in the industry
- Reduces vehicle bounce, loping and power hop
- Low aspect ratio for stability

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
G9H479	LSW430R38	LSW AG49H	TL	144A8/B	36	30	6,150	14	16.9	58.6	26.5	177	190E	265	60
G9H752	LSW525R50	LSW AG49H	TL	155A8/B	24	30	8,550	18	20.8	76.2	34.9	225	422	466	66
G8M716	LSW1100R46	LSWAG49M	TL	177A8/B	23	30	16,100	38	43.3	85	38.9	251	697	1248	77

*See Approved Rim Contours section

Bias R-2

Titan



Titan Special Service R-2

- At its best in muddy, sticky soil conditions
- Curved lugs prevent mud clogging while adding traction and side hill slip resistance

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
47B628	13.6-38	Special Service	TT	6	22	25	3,300	12	14.3	61.9	28.9	186	241E	176	78
47B638	14.9-28	Special Service	TT	6	20	25	3,200	13	15.6	54.7	25.1	165	180E	165	89
47B674	15.5-38	Special Service	TT	6	20	25	3,520	14	15.9	64.2	29.9	193	172E	226	85
48B046	16.9-26	Special Service	TL	10	28	25	4,540	15	17.5	55.5	25.2	167	200E	229	96
48B056	18.4-26	Special Service	TL	10	26	25	5,200	16	18.8	57.5	26.1	173	236E	268	98
48B650	18.4-30	Special Service	TL	6	16	25	4,180	16	18.9	62.7	28.6	188	277E	316	99
47B654	18.4-34	Special Service	TT	6	16	25	4,400	16	18.9	66	30.3	198	290E	276	99
47B877	18.4-38	Special Service	TT	8	20	25	5,360	16	18.6	70.2	32.3	210	300E	323	99
47B889	20.8-38	Special Service	TT	8	18	25	6,150	18	20.2	72.8	33.4	218	385E	383	104
47B089	20.8-38	Special Service	TT	10	22	25	6,950	18	20.2	72.8	33.4	218	385E	391	104
47B886	23.1-26	Special Service	TT	8	16	25	5,680	20	23	65.2	29.3	194	291E	392	109
48B086	23.1-26	Special Service	TL	10	20	25	6,400	20	23	65.2	29.3	194	291E	423	109
47B882	23.1-30	Special Service	TT	8	16	25	6,000	20	23.5	68.6	31	205	298E	401	109
47B888	23.1-34	Special Service	TT	8	16	25	6,400	20	23.5	72.6	33	216	310E	412	109
47B099	24.5-32	Special Service	TT	10	20	25	7,850	21	24.5	72.1	32.6	215	320E	511	112
48B198	28L-26	Special Service	TL	12	20	25	7,400	25	28.4	64.3	28.9	192	408E	502	109
48B096	30.5L-32	Special Service	TL	10	16	25	8,250	27	29.8	73.4	33.2	218	500E	638	113
48B196	30.5L-32	Special Service	TL	12	20	25	9,350	27	29.8	73.4	33.2	218	500E	682	113
48B396	30.5L-32	Special Service	TL	14	22	25	9,900	27	29.8	73.4	33.2	218	500E	683	113

*See Approved Rim Contours section

Radial R-3

Titan



TORC TRAC



TORC TRAC II

Titan Torc Trac Radial R-3

- Minimizes ground disturbance with its wide, flat footprint and deep grooves
- Performance proven as an original equipment tire

Titan Torc Trac II Radial R-3

- Features radial construction for reduced rolling resistance, increased footprint area and reduced fuel consumption

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
48G556	18.4R26	Torc Trac Radial	TL	146A8/B	32	30	6,600	16	19.1	55.4	24.7	166	na	281	29
48G686	23.1R26	Torc Trac Radial	TL	161A8/B	42	30	10,200	20	22.8	59.6	26.8	175	245	431	31
48G798	28LR26	Torc Trac II Radial	TL	174A8/B	54	30	14,800	25	28	62.6	27.8	184	419	493	30
48G796	30.5LR32	Torc Trac II Radial	TL	181A8/B	52	30	18,200	27	29.5	70.5	32	209	572	718	37

*See Approved Rim Contours section

Titan

Bias R-3



TORC TRAC



TORC TRAC II

Titan Torc Trac R-3

- Minimizes ground disturbance with its wide, flat footprint and deep grooves
- Performance proven as an original equipment tire

Titan Torc Trac II R-3

- This rugged tire minimizes ground disturbance with a button tread pattern that offers good performance on vibratory rollers and combine applications

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
475412	12.4-28	Torc Trac II	TT	4	16	25	1,980	11	12.9	47.5	22.1	141	145E	87	22
475612	12.4-28	Torc Trac II	TT	6	24	25	2,540	11	12.9	47.5	22.1	141	145E	93	22
485363	12-16.5NHS	Torc Trac	TL	8	50	5	3,270	9.75	11.8	33.1	14.9	98	110E	71	23
485424	13.6-28	Torc Trac II	TL	4	14	25	2,200	12	14	50.8	23.5	151	160E	107	24
475624	13.6-28	Torc Trac II	TT	6	22	25	2,830	12	14	50.8	23.5	151	160E	102	24
475634	14.9-24	Torc Trac	TT	6	20	25	3,000	13	15.2	48.4	212.1	144	157E	132	27
485834	14.9-24	Torc Trac	TL	8	26	25	3,520	13	15.2	48.4	212.1	144	157E	142	27
485034	14.9-24	Torc Trac	TL	10	32	25	3,960	13	15.2	48.4	212.1	144	157E	156	27
485343	33x15.50-16.5NHS	Torc Trac	TL	12	60	25	6,600	12	14.2	32.8	14.7	98	128	93	23
485645	16.9-24	Torc Trac	TL	6	18	25	3,420	15	17.7	51.4	22.9	151	196E	159	28
485845	16.9-24	Torc Trac	TL	8	24	25	4,080	15	17.7	51.4	22.9	151	196E	159	28
485045	16.9-24	Torc Trac	TL	10	28	25	4,400	15	17.7	51.4	22.9	151	196E	173	28
485345	16.9-24	Torc Trac	TL	14	40	25	5,520	15	17.7	51.4	22.9	151	196E	179	28
485690	18.4-16.1	Torc Trac	TL	6	16	25	2,540	16	19.3	43.2	19.3	128	135E	139	29
485056	18.4-26	Torc Trac	TL	10	26	25	5,200	16	19.1	55.8	25.4	165	224E	244	29
485156	18.4-26	Torc Trac	TL	12	32	25	5,840	16	19.1	55.8	25.4	165	224E	249	29
485756	18.4-26	Torc Trac	TL	18	46	25	7,400	16	19.1	55.8	25.4	165	224E	262	29
48A886	23.1-26	Torc Trac II	TL	8	16	25	5,680	20	22.8	59.6	26.8	175	394E	293	31
48A086	23.1-26	Torc Trac II	TL	10	20	25	6,400	20	22.8	59.6	26.8	175	394E	304	31
48A586	23.1-26	Torc Trac II	TL	16	34	25	8,800	20	22.8	59.6	26.8	175	394E	333	31
485086	23.1-26	Torc Trac	TL	10	20	25	6,400	20	24	61.7	27.8	182	394E	332	35
485186	23.1-26	Torc Trac	TL	12	24	25	7,150	20	24	61.7	27.8	182	394E	358	35
485199	24.5-32	Torc Trac II	TL	12	24	25	8,800	21	24.2	69.9	32.4	211	327E	431	35
485599	24.5-32	Torc Trac II	TL	16	30	25	11,000	21	24.2	69.9	32.4	211	327E	431	35
485198	28L-26	Torc Trac II	TL	12	20	25	7,400	25	28	62.6	27.8	184	443E	430	30
485598	28L-26	Torc Trac II	TL	16	28	25	9,900	25	28	62.6	27.8	184	443E	465	30
485196	30.5L-32	Torc Trac II	TL	12	20	25	9,350	27	29.5	70.5	32	209	564E	536	37
485596	30.5L-32	Torc Trac II	TL	16	26	25	11,000	27	29.5	70.5	32	209	564E	566	37

*See Approved Rim Contours section

Titan

Bias R-4



Titan Grizz LSWG9F R-4

- This LSW low profile tire is designed to reduce bounce and road lope as well as better sway-action recovery, while using 25-30% less urethane than a standard tire

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
G9F161	LSW495-762	LSW G9F	TL	12	34	25	7,600	15	19	51.6	24	155	na	225	34

*See Approved Rim Contours section

Bias R-4

Titan



Titan Industrial Tractor Lug R-4 Titan Industrial Contractor R-4

- Extra wide lugs with extensive overlap at the center, designed to resist buckling, tearing and cracking
- Excellent tread wear and roadability, the laterally designed lugs result in even wear



Titan Industrial Tractor Lug II R-4

- Features increased contact area for better traction and superior compound for improved abrasion resistance

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
486634	14.9-24	Industrial Tractor	TL	6	24	25	4,300	13	15.3	48.1	22	143	140E	145	34
486834	14.9-24	Industrial Tractor	TL	8	30	25	5,080	13	15.3	48.1	22	143	140E	145	34
486034	14.9-24	Industrial Tractor	TL	10	36	25	5,680	13	15.3	48.1	22	143	140E	160	34
486134	14.9-24	Industrial Tractor	TL	12	42	25	6,400	13	15.3	48.1	22	143	140E	164	34
4866T2	420/70-24	Industrial Tractor	TL	6	20	25	3,960	13	16.5	46.4	21.1	137	165E	151	35
486845	16.9-24	Industrial Tractor	TL	8	28	25	5,840	15	17.4	50.6	23	153	194E	160	35
486045	16.9-24	Industrial Tractor	TL	10	32	25	6,400	15	17.4	50.6	23	153	194E	168	35
486145	16.9-24	Industrial Tractor	TL	12	38	25	7,150	15	17.4	50.6	23	153	194E	173	35
486345	16.9-24	Industrial Tractor	TL	14	44	25	7,850	15	17.4	50.6	23	153	194E	174	35
486848	16.9-28	Industrial Tractor	TL	8	28	25	6,150	15	17.4	54.6	25	162	223E	178	34
486048	16.9-28	Industrial Tractor	TL	10	32	25	6,800	15	17.4	54.6	25	162	223E	193	34
486148	16.9-28	Industrial Tractor	TL	12	38	25	7,600	15	17.4	54.6	25	162	223E	198	34
486003	17.5L-24	Industrial Tractor	TL	10	32	25	6,150	15	17.1	48.8	22.3	145	192E	161	32
486103	17.5L-24	Industrial Tractor	TL	12	36	25	6,600	15	17.1	48.8	22.3	145	192E	169	32
4D6003	17.5L-24	Industrial Contractor	TL	10	32	25	6,150	15	17.1	48.8	22.3	145	192E	161	32
486603	17.5L-24	Industrial Tractor	TL	6	20	25	4,400	15	17.1	48.8	22.3	145	192E	148	32
486803	17.5L-24	Industrial Tractor	TL	8	26	25	5,360	15	17.1	48.8	22.3	145	192E	148	32
4D6603	17.5L-24	Industrial Contractor	TL	6	20	25	4,400	15	17.1	48.8	22.3	145	192E	148	32
4D6103	17.5L-24	Industrial Contractor	TL	12	36	25	6,600	15	17.1	48.8	22.3	145	192E	169	32
486864	18.4-24	Industrial Tractor	TL	8	24	25	6,400	16	18.8	53.8	24.4	160	246E	189	35
486164	18.4-24	Industrial Tractor	TL	12	36	25	8,250	16	18.8	53.8	24.4	160	246E	211	35
486056	18.4-26	Industrial Tractor	TL	10	30	25	7,600	16	18.8	55.8	25.1	166	252E	235	35
486156	18.4-26	Industrial Tractor	TL	12	36	25	8,800	16	18.8	55.8	25.1	166	252E	235	35
486058	18.4-28	Industrial Tractor	TL	10	30	25	7,850	16	18.8	57.8	26.4	172	256E	220	35
49F161	19.5L-24	Industrial Tractor II	TL	12	34	25	7,600	17	19	51.6	24	155	206E	198	34
486861	19.5L-24	Industrial Tractor	TL	8	24	25	6,000	17	19.1	51.8	23.5	154	206E	180	34
486061	19.5L-24	Industrial Tractor	TL	10	28	25	6,600	17	19.1	51.8	23.5	154	206E	192	34
486161	19.5L-24	Industrial Tractor	TL	12	34	25	7,600	17	19.1	51.8	23.5	154	206E	198	34
486075	21L-24	Industrial Tractor	TL	10	26	25	7,400	18	21	54.3	24.6	161	238E	250	35
486175	21L-24	Industrial Tractor	TL	12	32	25	8,550	18	21	54.3	24.6	161	238E	250	35
486076	21L-28	Industrial Tractor	TL	10	22	25	5,080	18	21	58.3	26.6	173	260E	303	36
486376	21L-28	Industrial Tractor	TL	14	36	25	9,900	18	21	58.3	26.6	173	260E	334	36

*See Approved Rim Contours section

Titan

Bias F-1



Titan Tru-Trac Front Tractor F-1

- Penetrates deep into soil for maximum steering control and minimal lateral side-slip because of its high center rib
- Used by original equipment manufacturers and offers excellent durability

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
4602U4	12.4-30SL	Single Rib	TL	10	40	25	3,520	12	13.5	53.5	24.5	159	na	116	na

*See Approved Rim Contours section

Titan

Bias F-2/F-2M



Titan Tru-Trac F-2

- Penetrates deep into soil for maximum steering control and minimal lateral side-slip because of its high center rib
- Used by original equipment manufacturers and offers excellent durability



Titan Tru-Trac Multi Rib F-2M

- Best for handling heavy loads on hard-packed surfaces
- Offers excellent load distribution and flotation
- Features a nylon carcass, durable tread compound and bead rim shield

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
461229	4.00-12SL	Tru-Trac	TT	4	52	25	495	3	5	21.3	10	64	15E	11	15
461329	4.00-12SL	Tru-Trac	TL	4	52	25	495	3	5	21.3	10	64	15E	11	15
461230	4.00-15SL	Tru-Trac	TT	4	52	25	585	3	4.6	24.6	11.6	73	17E	12	14
461233	4.00-19SL	Tru-Trac	TT	4	52	25	715	3	4.6	28.8	13.7	86	19E	14	14
462235	5.00-15SL	Tru-Trac	TT	4	44	25	715	3	5.5	26	12.2	77	25E	14	16
462335	5.00-15SL	Tru-Trac	TL	4	44	25	715	3	5.5	26	12.2	77	25E	16	16
462334	5.00-15SL	Tru-Trac	TL	6	64	25	910	3	5.5	26	12.2	77	25E	17	16
462238	5.50-16SL	Tru-Trac	TT	4	40	25	855	4	6.3	27.9	13.1	83	29E	17	17
462338	5.50-16SL	Tru-Trac	TL	4	40	25	855	4	6.3	27.9	13.1	83	29E	19	17
462239	5.50-16SL	Tru-Trac	TT	6	56	25	1,050	4	6.3	27.9	13.1	83	29E	19	17
462274	6.00-16SL	Tru-Trac	TT	4	36	25	910	4	6.7	29	13.6	86	36E	20	18
462275	6.00-16SL	Tru-Trac	TT	6	52	25	1,140	4	6.7	29	13.6	86	36E	21	18
462375	6.00-16SL	Tru-Trac	TL	6	52	25	1,140	4	6.7	29	13.6	86	36E	22	18
462281	6.50-16SL	Tru-Trac	TT	6	48	25	1,230	4.5	7.3	29.8	13.9	89	41E	24	20
462381	6.50-16SL	Tru-Trac	TL	6	48	25	1,230	4.5	7.3	29.8	13.9	89	41E	26	20
462283	7.50-16SL	Tru-Trac	TT	6	44	25	1,480	5.5	8.6	31.6	14.7	94	48E	29	23
462284	7.50-16SL	Tru-Trac	TT	8	56	25	1,710	5.5	8.6	31.6	14.7	94	48E	32	23
466383	7.50-16SL	Tru Trac Multi Rib	TL	6	44	25	1,480	5.5	8.6	31.3	14.6	93	34E	35	21
462278	7.50-18SL	Tru-Trac	TT	6	44	25	1,610	5.5	8.6	33.9	15.8	101	52E	33	23
462393	7.50-20SL	Tru-Trac	TL	6	44	25	1,710	5.5	8.6	35.8	16.8	107	57E	43	23
462290	7.5L-15SL	Tru-Trac	TT	6	44	25	1,430	6	8.1	29.3	13.6	87	33E	28	24

Bias F-2/F-2M

Titan

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
462390	7.5L-15SL	Tru-Trac	TL	6	44	25	1,430	6	8.1	29.3	13.6	87	33E	30	24
462244	9.5L-15SL	Tru-Trac	TT	8	48	25	1,870	7	9.9	31.5	14.6	93	53E	41	27
466343	9.5L-15SL	Tru Trac Multi Rib	TL	6	45	25	1,520	7	9.9	31.5	14.6	93	53E	46	27
462343	9.5L-15SL	Tru-Trac	TL	6	36	25	1,520	7	9.9	31.5	14.6	93	53E	41	27
462294	10.00-16SL	Tru-Trac	TT	6	32	25	1,930	8	10.8	35.6	16.4	105	67E	49	30
462394	10.00-16SL	Tru-Trac	TL	6	32	25	1,930	8	10.8	35.6	16.4	105	67E	51	30
466394	10.00-16SL	Tru Trac Multi Rib	TL	6	32	25	1,930	8	11.2	35.5	16.4	105	67E	55	28
466298	10.00-16SL	Tru Trac Multi Rib	TT	8	44	25	2,340	8	11.2	35.5	16.4	105	67E	56	28
462398	10.00-16SL	Tru-Trac	TL	8	44	25	2,340	8	10.8	35.6	16.4	105	67E	55	30
466398	10.00-16SL	Tru Trac Multi Rib	TL	8	44	25	2,340	8	11.2	35.5	16.4	105	67E	59	28
462295	11.00-16SL	Tru-Trac	TT	8	40	25	2,600	10	12.3	38.3	17.6	113	75E	72	33
462395	11.00-16SL	Tru-Trac	TL	8	40	25	2,600	10	12.3	38.3	17.6	113	75E	76	33
466295	11.00-16SL	Tru Trac Multi Rib	TT	8	40	25	2,600	10	12.7	38.1	17.5	112	84E	76	28
466396	11.00-16SL	Tru Trac Multi Rib	TL	12	60	25	3,420	10	12.7	38.1	17.5	112	84E	85	28
466395	11.00-16SL	Tru Trac Multi Rib	TL	8	40	25	2,600	10	12.7	38.1	17.5	112	84E	80	28
466347	11.00-20SL	Tru Trac Multi Rib	TL	12	60	25	3,860	10	12.4	41.5	19.2	123	85E	99	28
466348	11.00-24SL	Tru Trac Multi Rib	TL	8	40	25	3,420	10	12.4	45.5	21.2	155	90E	102	28
462218	11L-15SL	Tru-Trac	TT	8	44	25	2,090	8	10.8	32.1	14.9	95	53E	52	31
466318	11L-15SL	Tru Trac Multi Rib	TL	8	44	25	2,090	8	10.9	31.8	14.7	94	59E	71	27
462287	14L-16.1SL	Tru-Trac	TT	8	36	25	3,000	11	14.8	40	18.3	118	90E	97	44
466389	14L-16.1SL	Tru Trac Multi Rib	TL	10	44	25	3,420	11	14.4	38.4	17.6	113	100E	106	32
466352	16.5L-16.1SL	Tru Trac Multi Rib	TL	10	40	25	4,080	14	17.3	42.2	19.3	124	143E	150	36

*See Approved Rim Contours section

Bias F-3

Titan



Titan Contractor F-3

- Low section height design for loader backhoe applications
- Designed for excellent durability and good road handling characteristics



Titan Industrial Front Tractor F-3

- Designed for excellent durability
- Good road handling characteristics for industrial service

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
465318	11L-15SL	Contractor	TL	8	44	25	2,090	8	11	31.3	14.5	93	56E	51	15
465310	11L-15SL	Contractor	TL	10	52	25	2,340	8	11	31.3	14.5	93	56E	52	15
465315	11L-16SL	Contractor	TL	10	52	25	2,470	8	11	32.3	15	96	60E	53	15
465317	11L-16SL	Contractor	TL	12	64	25	2,760	8	11	32.3	15	96	60E	59	15
464396	11.00-16SL	Industrial Front Tractor	TL	12	60	25	3,420	10	12.2	36.1	16.6	107	82E	74	15
465388	14.5/75-16.1SL	Contractor	TL	10	40	25	3,200	11	13.7	35.5	16.4	105	120E	74	18
4653Q3	480/45-17	Contractor	TL	10	42	30	6,160	16	19.3	34	15.4	101	150E	85	na

*See Approved Rim Contours section

Titan

Bias I-1



DURA LIFE



HI FLOTATION

Titan Dura Life I-1

- This popular OEM tire offers wide ribs for good ground contact and excellent treadwear
- Straight ahead directional control is maximized with a series of straight circumferential grooves and ribs

Titan Hi Flotation I-1

- Noted for its maximum flotation
- Features wide tread design, large footprint, deep grooves and low section height design



PACKER



PLANTER AG41B

Titan Packer I-1

- Developed for the latest air seeders to firm the soil after the seed has been put into place
- This tire can operate at inflation pressures of 6 to 45 PSI, depending on soil conditions

Titan Planter AG41B I-1

- Designed to minimize seed bed compaction
- Open center and ribs at tread edge straddle seed placement location
- Features one rib in each shoulder

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
418277	4.00-12SL	Dura Life	TT	4	44	30	675	3	5	20.4	9.5	60	na	7	5
418249	4.00-9SL	Dura Life	TT	4	44	30	550	3	4.8	17.4	7.9	51	na	5	5
41M353	5.90-15SL	Dura Life	TL	4	36	30	1,140	4.5	6.3	26.6	12.1	79	na	17	7
418353	5.90-15SL	Dura Life	TL	4	36	30	1,140	4.5	6.3	26.6	12.1	79	na	17	7
418281	6.50-16SL	Dura Life	TT	6	44	30	1,710	4.5	6.9	28.7	13	85	na	22	7
418367	6.70-15SL	Dura Life	TL	4	32	30	1,280	4.5	7	28.3	12.8	84	na	19	7
418288	6.70-15SL	Dura Life	TT	6	44	30	1,610	4.5	7	28.3	12.8	84	na	19	7
41M388	6.70-15SL	Dura Life	TL	6	44	30	1,710	4.5	7	28.3	12.8	84	na	21	7
418284	7.50-16SL	Dura Life	TT	8	48	30	2,340	5.5	8.4	31	13.9	92	na	29	8
41B301	7.50-20SL	Planter	TL	4	28	30	1,760	5.5	8.7	37.2	17	110	na	36	22
41A301	7.50-20SL	Planter	TL	6	36	30	2,090	5.5	8.1	34.9	16.4	104	na	36	18
41A3X7	7.50-20SL	Planter	TL	8	48	30	2,540	5.5	8.1	34.9	16.4	104	na	43	18
418336	7.60-15SL	Dura Life	TL	6	40	30	1,760	5.5	8.1	28.5	12.8	84	na	25	8
418337	7.60-15SL	Dura Life	TL	8	52	30	2,090	5.5	8.1	28.5	12.8	84	na	27	8
410289	8.5L-14SL	Hi Flotation	TT	6	36	30	1,870	6	8.6	28.6	12.8	84	na	26	11
410389	8.5L-14SL	Hi Flotation	TL	6	36	30	1,870	6	8.6	28.6	12.8	84	na	28	11
418248	9.00-16SL	Dura Life	TT	10	52	30	3,300	6	9.3	32.7	14.6	96	na	40	10
4183J8	9.00-24SL	Dura Life	TL	8	40	30	3,520	8	10.5	42.3	19.2	125	na	66	10
41M3J8	9.00-24SL	Dura Life	TL	8	40	30	3,520	8	10.5	42.3	19.2	125	na	66	10
410299	9.5L-14SL	Hi Flotation	TT	8	44	30	2,400	7	9.8	29.2	13	86	na	29	11
41L399	9.5L-14SL	Hi Flotation	TL	8	44	30	2,400	7	9.8	29.2	13	86	na	30	11
410298	9.5L-14SL	Hi Flotation	TT	6	32	30	1,930	7	9.8	29.2	13	86	na	26	11
410398	9.5L-14SL	Hi Flotation	TL	6	32	30	1,930	7	9.8	29.2	13	86	na	28	11
410399	9.5L-14SL	Hi Flotation	TL	8	44	30	2,400	7	9.8	29.2	13	86	na	30	11
410343	9.5L-15SL	Hi Flotation	TL	6	32	30	2,040	7	9.8	39.2	13.5	89	na	32	11
410244	9.5L-15SL	Hi Flotation	TT	8	44	30	2,470	7	9.8	30.2	13.5	89	na	32	11
4102D7	9.5L-15SL	Hi Flotation	TT	12	64	30	3,200	7	9.8	30.2	13.5	89	na	37	11
410344	9.5L-15SL	Hi Flotation	TL	8	44	30	2,470	7	9.8	30.2	13.5	89	na	34	11

Bias I-1

Titan

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
4183L1	10.00-15SL	Dura Life	TL	8	40	25	3,200	8	10.9	33.5	14.8	99	na	47	11
4183K7	11.25-24SL	Dura Life	TL	8	32	30	4,080	10	12.6	45.7	20.6	135	na	91	11
410364	11L-14SL	Hi Flotation	TL	6	28	30	2,040	8	10.7	30	13.3	88	na	32	11
410314	11L-15SL	Hi Flotation	TL	6	28	30	2,150	8	10.8	31	13.3	92	na	35	11
410218	11L-15SL	Hi Flotation	TT	8	36	30	2,540	8	10.8	31	13.3	92	na	35	11
41L318	11L-15SL	Hi Flotation	TL	8	36	30	2,540	8	10.8	31	13.3	92	na	38	11
410319	11L-15SL	Hi Flotation	TL	10	44	30	2,910	8	10.8	31	13.3	92	na	43	11
410317	11L-15SL	Hi Flotation	TL	12	52	30	3,200	8	10.8	31	13.3	92	na	49	11
41L315	11L-15SL	Hi Flotation	TL	18	80	30	4,180	8	10.8	31	13.3	92	na	59	11
410318	11L-15SL	Hi Flotation	TL	8	36	30	2,540	8	10.8	31	13.3	92	na	38	11
410222	11L-16SL	Hi Flotation	TT	8	36	30	2,680	8	10.7	32	14.3	95	na	40	11
410340	12.5L-15SL	Hi Flotation	TL	8	36	30	3,000	10	12.1	32.1	14.3	95	na	47	11
410241	12.5L-15SL	Hi Flotation	TT	10	44	30	3,420	10	12.1	32.1	14.3	95	na	48	11
41L305	12.5L-15SL	Hi Flotation	TL	12	52	30	3,860	10	12.1	32.1	14.3	95	na	52	11
41L327	12.5L-15SL	Hi Flotation	TL	20	80	30	5,080	10	12.1	32.1	14.3	95	na	68	11
410341	12.5L-15SL	Hi Flotation	TL	10	44	30	3,420	10	12.1	32.1	14.3	95	na	47	11
410305	12.5L-15SL	Hi Flotation	TL	12	52	30	3,860	10	12.1	32.1	14.3	95	na	52	11
410253	12.5L-16SL	Hi Flotation	TT	14	56	30	4,180	10	11.9	31.9	14.3	95	na	53	11
41L353	12.5L-16SL	Hi Flotation	TL	14	56	30	4,180	10	11.9	31.9	14.3	95	na	56	11
410262	14L-16.1SL	Hi Flotation	TT	12	44	30	4,680	11	14.8	37.4	16.5	110	na	76	12
41L3L2	14L-16.1SL	Hi Flotation	TL	14	52	30	5,200	11	14.8	37.4	16.5	110	na	91	12
410368	14L-16.1SL	Hi Flotation	TL	8	32	30	3,860	11	14.8	37.4	16.5	110	na	72	12
41L368	14L-16.1SL	Hi Flotation	TL	8	32	30	3,860	11	14.8	37.4	16.5	110	na	72	12
410350	16.5L-16.1SL	Hi Flotation	TL	10	36	30	5,200	14	17.1	40.9	18	120	na	102	14
41L350	16.5L-16.1SL	Hi Flotation	TL	10	36	30	5,200	14	17.1	40.9	18	120	na	102	14
4103L1	16.5L-16.1SL	Hi Flotation	TL	14	48	30	6,400	14	17.1	40.9	18	120	na	116	14
410348	16.5L-16.1SL	Hi Flotation	TL	8	28	30	4,400	14	17.1	40.9	18	120	na	99	14
4103H7	19L-16.1SL	Hi Flotation	TL	10	32	30	6,000	16	19.1	43.6	18.9	127	na	131	17
4105H7	19L-16.1SL	Hi Flotation	TL	12	36	30	6,600	16	19.1	43.6	18.9	127	na	144	17
41M356	20.5/5.5-12	Packer	TL	4	36	30	740	4	5.8	20.6	9.4	61	na	15	8
410349	21.5L-16.1SL	Hi Flotation	TL	10	28	30	6,600	18	21.4	45.0	19.9	135	na	171	17
4103J1	21.5L-16.1SL	Hi Flotation	TL	14	36	30	7,850	18	21.4	45	19.9	135	na	176	17
4103Q4	21.5L-16.1SL	Hi Flotation	TL	18	44	30	8,800	18	21.4	45	19.9	135	na	181	17
41M355	26/6.50-15	Packer	TL	4	45	30	1,400	4.5	6.5	26.4	12.1	78	na	26	11
41M32T	26/7.75-15	Packer	TL	4	45	30	1,610	4.5	6.5	26.4	12.1	78	na	28	11
410361	26x12.00-12NHS	Hi Flotation	TL	4	20	30	1,780	8	11.7	25.5	11	77	na	30	12

*See Approved Rim Contours section



Titan Grizz LSW 410/411 I-1

- Patented wheel and tire assembly designed to reduce vehicle bounce, reduce loping and provides excellent stability on towed implements

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
G1L3L1	LSW420-648	LSW 410	TL	14	48	30	6,400	356	15.2	40.2	18.7	120	na	118	14
G1L350	LSW420-648	LSW 410	TL	10	36	30	5,200	356	15.2	40.2	18.7	120	na	105	14

*See Approved Rim Contours section

Titan

Bias I-3



CONTRACTOR



CONTRACTOR II

Titan Contractor I-3

- An implement tire specially designed for high traction applications
- Frequently used on the front of backhoes, this tire is available in 10-ply construction

Titan Contractor II I-3

- A new, more robust design for use on the front of large backhoes



TI422



TRACTION IMPLEMENT

Titan TI422 I-3

- Designed for low horsepower traction requirements, the Traction Implement offers good roadability and excellent durability

Titan Traction Implement I-3

- Designed for low horsepower traction requirements, the Traction Implement offers good roadability and excellent durability

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
422303	7.50-20SL	Traction Implement	TL	4	28	25	1,760	5.5	8.1	34.9	15.9	104	na	38	17
422204	7.50-24SL	Traction Implement	TT	4	28	25	1,870	7	8.7	38.9	17.9	115	na	41	17
46W3X8	10.5/80-18	Contractor	TL	6	33	25	2,830	9	10.8	35.7	16.5	109	na	70	29
46W3J8	10.5/80-18	Contractor	TL	10	54	25	3,840	9	10.8	35.7	16.5	109	na	71	29
46W3J9	12.5/80-18	Contractor	TL	10	46	25	4,710	9	12	38.8	17.4	114	na	98	31
4223J9	12.5/80-18	TI422	TL	10	46	25	4,710	9	12	38.8	17.4	114	na	86	34
42E3J9	12.5/80-18	Contractor II	TL	10	46	25	4,710	9	12	39.1	18	117	na	88	32
42E3T7	12.5/80-18	Contractor II	TL	12	56	25	5,360	9	12	39.1	18	117	na	91	32
46W39N	12.5/80-18	Contractor	TL	6	28	25	3,420	9	12	38.8	17.4	114	na	92	31
499505	13.50-16.1SL	Traction Implement	TL	6	24	25	3,520	11	13.5	40.8	17.8	120	na	83	23
4223M2	16.5L-16.1SL	TI422	TL	6	24	25	3,960	14	16.5	40	17.7	117	na	96	26
4223W6	16.5L-16.1SL	TI422	TL	10	36	25	5,200	14	16.5	40	17.7	117	na	106	26
4223M3	21.5L-16.1SL	TI422	TL	8	24	25	6,000	18	20.3	44.6	19.6	132	na	151	35

*See Approved Rim Contours section



Titan Grizz LSW G2E I-3

- Designed for the front position of large backhoes
- This LSW size can replace the popular 12.5/80-18 front backhoe tire, yet gives LSW stability

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
G2E3T7	LSW320-597	LSW G2E	TL	12	56	25	5,360	9	12	39.1	18	117	na	114	32

*See Approved Rim Contours section

Bias FI

Titan



Titan Highway Implement FI

- Offers D.O.T. compliance for approved operation at highway speeds
- Noted for its great handling and towing characteristics

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
41H313	9.5L-15FI	Highway Implement	TL	D	60	Highway	2,680	8	9.8	30.2	13.5	89	na	41	11
41H383	11L-15FI	Highway Implement	TL	C	45	Highway	2,600	8	9.8	30.2	13.5	89	na	38	11
41H384	11L-15FI	Highway Implement	TL	E	75	Highway	3,560	8	9.8	30.2	13.5	89	na	48	11
41H392	11L-15FI	Highway Implement	TL	F	90	Highway	3,960	8	10.6	30.8	13.8	94	na	52	11
41H387	12.5L-15FI	Highway Implement	TL	F	90	Highway	4,680	10	12.1	32.1	14.3	95	na	65	11
41H382	13.50-15FI	Highway Implement	TL	C	30	Highway	2,680	10	13.5	31.8	14.4	96	na	60	11
41H3K0	13.50-15FI	Highway Implement	TL	E	60	Highway	3,960	10	13.5	31.8	14.4	96	na	72	11
41H3F0	13.50-15FI	Highway Implement	TL	F	75	Highway	4,540	10	13.5	31.8	14.4	96	na	77	11
41H388	14L-16.1FI	Highway Implement	TL	C	30	Highway	3,420	11	14.24	37.51	16.7	112	na	76	12

*See Approved Rim Contours section

Bias Smooth

Titan



Titan Road Roller/Road Roller II Smooth

- Constructed of superior heat resistant nylon fabric plies to promote heat dissipation
- Designed for maximum life, this tire is frequently the tire of choice for industrial compactor applications

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
3GR256F	7.50-15NHS	Road Roller II	TT	6	55	5	3,900	6	8.1	30.8	14.1	92	na	46	0 #
3GR252F	7.50-15NHS	Road Roller II	TT	12	110	5	5,860	6	8.1	30.8	14.1	92	na	56	0 #
3GR2E1F	7.50-15NHS	Road Roller II	TT	14	125	5	6,300	6	8.1	30.8	14.1	92	na	56	0 #
3GR3A2	8.5/90-15K	Road Roller II	TL	6	50	5	3,900	6	8.1	30.9	13.7	90	na	47	0 #
38R222F	9.00-20NHS	Road Roller	TT	12	90	5	8,950	7	10.2	39.8	18	117	na	112	0
38R283F	11.00-20NHS	Road Roller	TT	18	120	5	13,000	8	12.1	41.7	18.8	122	na	185	0

*See Approved Rim Contours section

#Tire rim fitment for these tires are not interchangeable. The 15K tire will only fit on a 5° drop center rim. The NHS tire is designed to fit on a 5° flat base rim. The 8.5/90-15K size designation was established to advise of this distinction.

Titan

Bias & Radial HF-1/HF-2



FLO-TRAC RIB



MULTI TRAC C/S

Titan Flo-Trac Rib HF-1

- Designed for maximum flotation and durability
- Low section height gives it improved handling
- Open curved lug design allows for maximum self-cleaning and side hill slip resistance

Titan Multi Trac C/S HF-1

- Greater tread depth and more rubber on the contact surface to provide increased puncture resistance and longer tire life
- Shoulder design minimizes turf damage



CLASSIC RIB



CLASSIC TX

Titan Classic Rib HF-1

- Specifically designed to reduce turf damage
- Good front end tire sporting a long-lasting, high performance rating

Titan Classic TX HF-1

- Landscaping projects, mowing and general grounds work are easily accomplished with this rugged tire, designed to take abuse
- Wide footprint endures heavy loads and provides stability and traction



Titan Soft Turf/LSW and LSW 430 HF-1

- Designed for low ground pressure use
- Ideal for fine lawn maintenance and can also be used for industrial applications
- Available in LSW
- The radial LSW430 is a patented wheel and tire assembly designed to reduce vehicle bounce, loping and sidewall heat build-up
- LSW430 features a low aspect ratio tire and a large diameter wheel



FLO-TRAC LUG



TRU POWER II

Titan Flo-Trac Lug HF-2

- Designed for maximum flotation and durability
- Features low section height for improved handling and roadability
- Open curved lug design allows for maximum self-cleaning and side hill slip resistance

Titan Tru Power II HF-2

- Ultimate deep-traction tire with a large contact area to provide the best traction
- A great performer on wet or dry surfaces
- Features a specially designed rim guard to keep debris from the bead seat area

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
474304	16x6.50-8NHS	Multi Trac	TL	4	28	10	620	5.375	6.4	15.8	7.1	48	na	8	9
4743Q1	16x6.50-8NHS	Multi Trac	TL	8	58	10	950	5.375	6.4	15.8	7.1	48	na	8	9
481331	18x8.50-8NHS	Classic TX	TL	4	22	Highway	815	7.00	8.1	17.8	7.8	51	na	12	11
483331	18x8.50-8NHS	Classic Rib	TL	4	22	Highway	815	7.00	8.4	17.6	7.7	51	na	11	7
482331	18x8.50-8NHS	Classic ST II	TL	4	22	Highway	815	7.00	8.4	18.2	7.9	52	na	12	4
4233U1	18x8.50-10NHS	Tru Power II	TL	4	22	10	830	7	7.8	18.5	8.8	56	na	14	16
4743U1	18x8.50-10NHS	Multi Trac	TL	4	22	10	830	7	8.2	17.9	8	53	na	14	10
474318	20X8.00-10NHS	Multi Trac	TL	4	24	10	895	6.5	8.1	19.9	8.9	59	na	16	10
4743X2	20X8.00-10NHS	Multi Trac	TL	8	62	10	1,550	6.5	8.1	20.1	9.1	59	na	16	10

Bias & Radial HF-1/HF-2

Titan

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
4743F1	22x9.00-12NHS	Multi Trac	TL	4	20	10	1,110	7	8.4	21.8	9.5	63	na	19	12
474367	23x10.50-12NHS	Multi Trac	TL	4	20	10	1,340	8.5	10.4	22.6	10	65	na	23	12
474353	23x10.50-12NHS	Multi Trac	TL	6	32	10	1,760	8.5	10.4	22.6	10	65	na	24	12
474301	23x8.50-12NHS	Multi Trac	TL	4	22	10	1,115	7	8.3	22.6	9.9	65	na	20	12
474372	23x8.50-12NHS	Multi Trac	TL	6	34	10	1,440	7	8.3	22.6	10.2	66	na	20	12
474324	24x8.50-14NHS	Multi Trac	TL	4	22	10	1,230	7	8.5	24.2	10.2	72	na	19	11
4303N8	25x10.50LL-15NHS	Soft Turf	TL	6	30	30	935	8.25	10.4	25.7	11.8	76	na	31	12
41F393	25x7.50-15NHS	Flo Trac Rib	TL	4	30	30	960	5.5	7.8	24.9	11.6	74	na	24	8
41F378	25x7.50-15NHS	Flo Trac Rib	TL	6	45	30	1,220	5.5	7.8	24.9	11.6	74	na	24	8
474339	25x8.50-14NHS	Multi Trac	TL	4	22	10	1,320	7	8.5	24.9	11.1	74	na	26	11
474371	25x8.50-14NHS	Multi Trac	TL	6	32	10	1,640	7	8.5	24.9	11.1	74	na	26	11
423361	26x12.00-12NHS	Tru Power II	TL	4	20	10	1,780	10.5	12.3	25.6	12	77	na	39	20
423360	26x12.00-12NHS	Tru Power II	TL	8	42	10	2,740	10.5	12.3	25.6	12	77	na	42	20
4233B0	26x12.00-12NHS	Tru Power II	TL	8	42	10	2,740	10.5	12.3	25.6	12	77	na	42	20
474361	26x12.00-12NHS	Multi Trac	TL	4	20	10	1,780	10.5	12.2	25.2	10.9	73	na	33	12
474377	26x12.00-12NHS	Multi Trac	TL	6	30	10	2,250	10.5	12.2	25.2	10.9	73	na	34	12
4743H6	27x10.50-15NHS	Multi Trac	TL	4	30	30	1,320	8.5	10.2	26.9	12.3	82	na	35	12
4743E0	27x10.50-15NHS	Multi Trac	TL	10	75	30	2,200	8.5	10.2	26.9	12.3	82	na	42	12
4303M7	27x12LL-15NHS	Soft Turf	TL	6	30	30	1,320	10	12	27.5	12.2	85	na	35	10
474348	27x8.50-15NHS	Multi Trac	TL	4	30	30	1,230	7	8.4	26.7	12.3	79	na	27	11
474356	27x8.50-15NHS	Multi Trac	TL	6	45	30	1,570	7	8.4	26.7	12.3	79	na	27	11
41F394	27x9.50-15NHS	Flo Trac Rib	TL	4	30	30	1,260	7	9.5	26.7	12.3	79	na	27	9
41F395	27x9.50-15NHS	Flo Trac Rib	TL	6	45	30	1,600	7	9.5	26.7	12.3	79	na	30	9
41F306	27x9.50-15NHS	Flo Trac Rib	TL	8	60	30	1,900	7	9.5	26.7	12.3	79	na	32	9
474358	28x8.50-15NHS	Multi Trac	TL	6	30	30	1,430	7	8.4	28	12.6	84	na	23	11
4743L5	29x12.50-15NHS	Multi Trac	TL	4	20	30	1,320	10	12.2	29.1	13	87	na	40	12
4743D4	29x12.50-15NHS	Multi Trac	TL	6	30	30	1,710	10	12.2	29.1	13	87	na	45	12
47434A	31x13.50-15NHS	Multi Trac	TL	4	20	30	1,650	10	13.9	31.5	14.1	94	na	50	12
4743U2	31x13.50-15NHS	Multi Trac	TL	8	45	30	2,600	10	13.9	31.5	14.1	94	na	55	12
4743U3	31x13.50-15NHS	Multi Trac	TL	10	60	30	3,080	10	13.9	31.5	14.1	94	na	65	12
41F396	31x13.50-15NHS	Flo Trac Rib	TL	6	30	30	2,090	10	13.5	31.8	14.4	94	na	56	10
41N396	31x13.50-15NHS	Flo Trac Rib	TL	6	30	30	2,090	10	13.5	31.8	14.4	94	na	56	10
41F397	31x13.50-15NHS	Flo Trac Rib	TL	8	45	30	2,620	10	13.5	31.8	14.4	94	na	60	10
41N397	31x13.50-15NHS	Flo Trac Rib	TL	8	45	30	2,620	10	13.5	31.8	14.4	94	na	60	10
41N307	31x13.50-15NHS	Flo Trac Rib	TL	10	60	30	3,080	10	13.5	31.8	14.4	94	na	70	10
41N3U9	31x13.50-15NHS	Flo Trac Rib	TL	14	90	30	3,960	10	13.5	31.8	14.4	94	na	75	10
41G3A4	31x15.50-15NHS	Flo Trac Lug	TL	8	45	30	2,740	13	15.7	32.1	14.9	98	26	74	22
41G3H1	33x12.50-15NHS	Flo Trac Lug	TL	8	45	30	3,300	10	12.8	33.3	15	100	na	61	27
4743J0	33x12.50-16.5NHS	Multi Trac	TL	4	30	30	2,305	9.75	12.4	32.7	14.7	98	na	55	12
4743C4	33x14.50-15NHS	Multi Trac	TL	4	20	30	2,090	10	14.5	33.2	15.4	101	na	69	12
4233L0	35x12.00-16.5NHS	Tru Power II	TL	4	25	10	2,450	9.75	11.8	34.9	16.5	104	na	72	29
41G3G3	35x19.00-16.1NHS	Flo Trac Lug	TL	12	55	30	4,180	16	17.8	35	16.4	104	na	97	40
474350	36x13.50-15NHS	Multi Trac	TL	4	20	30	2,600	10	15	36	16.1	106	na	68	12
41G3F1	38x18.00-20NHS	Flo Trac Lug	TL	10	45	30	3,430	14	17.7	40.6	18.4	121	na	132	40
41G3R6	38x18.00-20NHS	Flo Trac Lug	TL	14	65	30	4,300	14	17.7	40.6	18.4	121	na	141	40
474323	41x14.00-20NHS	Multi Trac	TL	4	25	30	3,080	11	14	42.4	18.9	126	na	100	22

Titan

Bias & Radial HF-1/HF-2

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
474342	44x18.00-20NHS	Multi Trac	TL	4	20	30	3,420	14	18.6	45	20.1	134	na	133	25
4743W1	44x18.00-20NHS	Multi Trac	TL	6	30	30	4,300	14	18.6	45	20.1	134	na	142	25
G3032K	LSW305-521	LSW Soft Turf	TL	6	30	30	2,340	210	12	33.5	14.7	98	na	54	10
G30373	LSW305R343	LSW 430	TL	111A8	32	30	2,400	229	11	26.9	12	80	na	33	8
G303H4	LSW570-648	LSW Soft Turf	TL	6	60	30	6,000	457	22.5	45.5	18.5	140	na	151	12
G303P0	LSW610R470	LSW 430	TL	125A8	30	30	3,640	483	23.7	40	17.8	119	na	151	12

*See Approved Rim Contours section

Titan

Bias Skid Steer



CONTRACTOR FWD



H/E

Titan Contractor FWD SS

- Excellent traction and wear are the benefits of the broad, curved lugs
- High strength construction gives it exceptional durability

Titan H/E SS

- The H/E is Titan's premium deep tread skid steer tire, designed for use in severe applications such as concrete planing, asphalt recycling, demolition areas, quarries, glass plants and scrap yards



HD2000



HD2000 II

Titan HD2000 SS

- Engineered with HD sidewalls to protect against abrasions, tears and punctures
- Improved dual tapered step lug wear and extended life

Titan HD2000 II SS

- Titan's premium conventional skid steer tire with deeper tread depth, premium compound, larger tread lugs, heavier sidewall and larger rim guard



TRAC LOADER



TRAC LOADER CHEVRON

Titan Trac Loader SS

- The tire preferred by major manufacturers of unloaders and skid steer equipment
- Constructed with a superior blend of natural and synthetic rubber
- Center lug design adds extra traction

Titan Trac Loader Chevron SS

- Features a chevron tread pattern with nylon fabric construction
- Intended for skid steer use

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
4123C2	5.70-12NHS	Trac Loader Chevron	TL	4	60	5	1,450	4.5	5.7	22.4	10.3	67	na	17	18
4123C5	7.00-15SS	Trac Loader Chevron	TL	6	60	5	3,180	5.5	8	29.9	13.5	88	na	38	18
4127K5	8.25-15NHS	Trac Loader Chevron	TL	6	50	5	3,860	6	9.4	33.2	14.9	98	na	53	18
49E3D1TYL	10-16.5NHS	HD2000II w/Tyreliner	TL	8	60	5	4,140	8.25	10.5	30.3	14.1	91	na	83	24
4393D1	10-16.5NHS	HD2000	TL	8	60	5	4,140	8.25	10.3	30.6	14.3	92	na	55	21
49E3D1	10-16.5NHS	HD2000II	TL	8	60	5	4,140	8.25	10.5	30.3	14.1	91	na	55	24
43H3R8	10-16.5NHS	H/E	TL	10	75	5	4,710	8.25	10.4	30.6	13.7	89	na	88	44
4123C8	10-16.5NHS	Trac Loader	TL	6	45	5	3,500	8.3	10.9	30.3	13.5	90	na	48	19

Bias Skid Steer

Titan

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
4393D1TYL	10-16.5NHS	HD2000 w/Tyrelynner	TL	8	60	5	4,140	8.25	10.3	30.6	14.3	92	na	74	21
4393J7TYL	12-16.5NHS	HD2000II w/Tyrelynner	TL	10	65	5	5,600	9.75	12.2	32.7	15	97	na	99	26
4393C9	12-16.5NHS	HD2000	TL	6	40	5	4,220	9.75	12.8	32.7	15.3	99	na	71	23
4393J7	12-16.5NHS	HD2000	TL	10	65	5	5,600	9.75	12.8	32.7	15.3	99	na	74	23
49E3J7	12-16.5NHS	HD2000II	TL	10	65	5	5,600	9.75	12.2	32.7	15	97	na	74	26
49E34R	12-16.5NHS	HD2000II	TL	14	90	5	6,780	9.75	12.2	32.7	15	97	na	82	26
43H34R	12-16.5NHS	H/E	TL	14	90	5	6,780	9.75	12	32.7	15	97	na	101	44
4123C9	12-16.5NHS	Trac Loader	TL	6	40	5	4,220	9.75	12.1	33.6	15.1	101	na	66	23
4123D2	12-16.5NHS	Trac Loader	TL	8	50	5	4,810	9.75	12.2	33.6	15.1	101	na	68	23
46C3E8	12-16.5NHS	Contractor FWD	TL	8	50	5	4,810	9.75	11.8	33.1	14.9	98	na	68	23
46C3J7	12-16.5NHS	Contractor FWD	TL	10	65	5	5,600	9.75	11.8	33.1	14.9	98	na	70	23
439396	14-17.5NHS	HD2000	TL	10	55	5	6,850	10.5	13.8	37.2	17.6	113	na	92	24
439349	14-17.5NHS	HD2000	TL	12	65	5	7,550	10.5	13.8	37.2	17.6	113	na	99	24
439384	14-17.5NHS	HD2000	TL	14	80	5	8,540	10.5	13.8	37.2	17.6	113	na	101	24
49E384	14-17.5NHS	HD2000II	TL	14	80	5	8,540	10.5	15.2	35.7	16.4	107	na	119	26
43H384	14-17.5NHS	H/E	TL	14	80	5	8,540	10.5	14.1	36.6	17	110	na	139	47
412334	14-17.5NHS	Trac Loader	TL	6	30	5	4,820	10.5	14	36.9	16.3	109	na	92	24
412396	14-17.5NHS	Trac Loader	TL	10	55	5	6,850	10.5	14	36.9	16.3	109	na	92	24
412384	14-17.5NHS	Trac Loader	TL	14	80	5	8,540	10.5	14.3	36.4	16.4	107	na	101	24
46C3G9	14-17.5NHS	Contractor FWD	TL	10	55	5	6,850	10.5	13.8	36.3	16.3	108	na	83	24
439336	15-19.5NHS	HD2000	TL	12	60	5	9,190	11.75	15.7	40.5	19.2	123	na	133	26
412373	15-19.5NHS	Trac Loader	TL	6	30	5	6,130	11.75	15.5	40.5	17.9	117	na	112	25
412336	15-19.5NHS	Trac Loader	TL	12	60	5	9,190	11.75	15.5	40.5	17.9	117	na	133	25
46C3H9	15-19.5NHS	Contractor FWD	TL	8	40	5	7,250	11.75	15.3	40.1	18	119	na	110	26
4123U1	18x8.50-10NHS	Trac Loader	TL	4	22	5	830	7	7.5	17.7	8.1	53	38	16	16
49E3W8	20x8.00-10NHS	HD2000II	TL	4	40	5	1,210	6	8.2	19.3	8.8	57	na	21	15
4393G8	23x8.50-12NHS	HD2000	TL	6	50	5	1,810	7	8.7	23.5	11	71	na	27	14
4123C3	23x8.50-12NHS	Trac Loader	TL	4	35	5	1,470	7	8.3	23	10.2	68	na	27	14
4123G8	23x8.50-12NHS	Trac Loader	TL	6	50	5	1,810	7	8.3	23	10.2	68	na	27	14
412388	23x8.50-14NHS	Trac Loader	TL	4	35	5	1,490	7	7.8	23.8	10.7	71	na	25	14
412379	25x8.50-14NHS	Trac Loader	TL	6	50	5	2,000	7	8.4	25.9	11.8	79	na	30	17
412361	26x12.0-12NHS	Trac Loader	TL	4	20	5	1,780	10.5	12.2	25.5	11.3	77	84	35	16
439378	27x10.50-15NHS	HD2000	TL	8	60	5	3,100	8.5	10.2	27.1	12.8	82	na	46	15
4123H7	27x10.50-15NHS	Trac Loader	TL	6	45	5	2,610	8.5	11	27.5	12.3	82	na	38	17
439377	27x8.50-15NHS	HD2000	TL	8	60	5	2,890	7	8.6	26.8	12.5	81	na	38	15
4123C6	27x8.50-15NHS	Trac Loader	TL	4	30	5	1,940	7	8.8	27	12.1	81	na	37	17
412339	27x8.50-15NHS	Trac Loader	TL	6	45	5	2,480	7	8.8	27	12.1	81	na	37	17
46C3J3	27x8.50-15NHS	Contractor FWD	TL	4	35	5	1,840	7	8.1	27.2	12.4	81	na	34	19
4123R3	28x8.50-15NHS	Trac Loader	TL	6	45	5	2,880	7	8.4	28	12.8	83	na	28	17
439381	30.5x12-16.5NHS	HD2000	TL	8	45	5	3,840	9.75	12.5	30.8	14	91	na	74	21
49E3L8	31x15.50-16.5NHS	HD2000II	TL	8	35	5	4,480	12	15.5	31	14.1	92	na	85	24
49E3X3	33x15.5-16.5NHS	HD2000II	TL	12	60	5	6,835	12	15.5	33	15	98	na	107	24
49E3R9	33x15.5-16.5NHS	HD2000II	TL	14	70	5	7,480	12	15.5	33	15	98	na	107	24
4123A5	43x16.00-20NHS	Trac Loader	TL	4	20	5	4,540	14	16	43.5	19.3	129	na	130	26

*See Approved Rim Contours section

Titan**ATV**

Titan 489 X/T Rears ATV

- The perfect complement to the 489X/T front, this tire provides excellent all-around traction in 2WD and 4WD applications
- Includes dimpled tread elements and six ply rated construction

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
4113A5001	AT22x11-10	489 X/T	TL	6	7	50	385	9.00	10.6	22.1	9.9	65	--	20	19
411327	AT23x10-10	489 X/T	TL	6	7	50	375	8.00	9.8	23.1	10.5	68	--	19	19
411330	AT23x10-12	489 X/T	TL	6	7	50	365	8.00	9.2	23.1	10.6	69	--	20	19
411307	AT23x7-10	489 X/T	TL	6	7	50	275	5.50	7.0	23.0	10.4	67	--	18	19
411326001	AT23x8-10	489 X/T	TL	6	7	50	300	6.50	8.0	23.2	10.6	69	--	15	19
411304001	AT23x8-11	489 X/T	TL	6	7	50	200	6.50	7.6	23.5	10.6	70	--	17	19
411329	AT23x8-12	489 X/T	TL	6	7	50	280	6.50	7.4	23.2	10.6	69	--	17	19
411328001	AT24x10-11	489 X/T	TL	6	7	50	395	7.00	10.1	24.1	10.8	70	--	23	19
411338001	AT24x11.5-10	489 X/T	TL	6	7	50	480	9.50	11.3	24.1	10.4	69	--	22	19
411305001	AT24x11-10	489 X/T	TL	6	7	50	440	9.00	11.0	24.3	10.9	72	--	24	19
411344	AT24x11-12	489 X/T	TL	6	7	50	430	9.00	10.3	24.3	10.9	71	--	23	19
411332001	AT24x8-11	489 X/T	TL	6	7	50	320	6.50	8.0	24.0	10.8	71	--	19	19
411337	AT24x8-12	489 X/T	TL	6	7	50	310	6.50	7.5	24.2	10.5	69	--	18	18
4113A9001	AT24x9-11	489 X/T	TL	6	7	50	365	7.00	9.1	24.2	11.1	72	--	21	19
411342	AT24x9-12	489 X/T	TL	6	7	50	355	8.00	9.0	23.8	10.8	68	--	19	19
411321	AT25x10-12	489 X/T	TL	6	7	50	420	8.00	10.5	25.2	11.2	74	--	24	19
411308	AT25x11-10	489 X/T	TL	6	7	50	455	9.00	10.9	25.3	11.3	74	--	26	19
411346	AT25x11-12	489 X/T	TL	6	7	50	455	9.00	10.9	25.3	11.3	74	--	24	19
411306	AT25x8-12	489 X/T	TL	6	7	50	340	6.50	7.5	25.1	11.2	74	--	18	19
411355	AT26x10-12	489 X/T	TL	6	7	50	440	8.00	10.1	25.8	11.6	76	--	24	19

*See Approved Rim Contours section



Titan 589 M/T Rears ATV

- Building on the heritage of the popular AT589, this second generation tire is designed for the serious ATV enthusiast
- Stepped lugs provide lug strength and stability
- Features the deepest lug depth available
- Titan's exclusive LSW 589 M/T design is now available to enhance the ATV experience, redefining traction and stability

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
45X332	AT24x8-11	589 M/T	TL	6	7	50	320	6.50	8.1	24.3	11.1	73	--	25	33
45X3V7	AT25x10-11	589 M/T	TL	6	7	50	355	7.00	9.8	25.4	11.3	74	--	31	36
45X321	AT25x10-12	589 M/T	TL	6	7	50	340	8.00	9.8	25.4	11.5	75	--	28	36
45X393	AT25x12-10	589 M/T	TL	6	7	50	495	8.00	11.5	25.4	11.3	74	--	37	36
45X3R1	AT25x8-11	589 M/T	TL	6	7	50	420	6.50	7.6	25.4	11.2	74	--	25	33
41R306	AT25x8-12	AT 589	TL	3*	7	50	340	6.50	8.0	25.4	11.4	75	--	24	28
45X306	AT25x8-12	589 M/T	TL	6	7	50	420	6.50	7.9	24.9	11.2	75	--	23	33
41R393	AT25x12-10	AT 589	TL	3*	7	50	495	8.00	11.5	25.4	11.3	74	--	33	33
45X361	AT26x12-12	589 M/T	TL	6	7	50	410	8.00	11.0	26.3	11.9	79	--	39	36
45X3P6	AT26x9-12	589 M/T	TL	6	7	50	520	7.00	9.2	26.3	11.9	79	--	36	36
G5X3T0	LSW230-394AT	LSW 589 M/T	TL	6	7	50	440	152.00	8.8	27.3	12.5	81	--	31	36

ATV

Titan

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
G5X3U0	LSW255-394AT	LSW 589 M/T	TL	6	7	50	465	152.00	9.9	27.3	12.5	81	--	32	36
45X3U0	AT27x11-12	589 M/T	TL	6	7	50	495	8.00	10.2	27.5	12.4	82	--	35	36
45X3T0	AT27x9-12	589 M/T	TL	6	7	50	440	6.50	8.9	27.4	12.4	82	--	35	36
45X35A	AT28x11x12	589 M/T	TL	6	7	50	535	8.00	10.1	28.2	12.7	84	--	36	36
45X34N	AT28x9x12	589 M/T	TL	6	7	50	465	6.50	8.8	28.0	12.7	84	--	36	36

*See Approved Rim Contours section



Titan Fast Trekker Rears ATV

- Developed specifically to address the demands of maneuverability
- The center V-lug provides straight ahead traction, while the S-knob cleats offer side bite on loose pack surfaces

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
46U3C3001	AT18x11-10	Fast Trekker	TL	3*	7	50	280	9.00	102.2	17.4	7.6	50	--	14	16
46U386001	AT18x11-8	Fast Trekker	TL	3*	7	50	290	9.00	10.6	17.7	8.2	53	--	14	16
46U346001	AT18x9.5-8	Fast Trekker	TL	3*	7	50	245	7.50	9.0	18.0	8.1	53	--	11	16
46U325001	AT20x10-10	Fast Trekker	TL	3*	7	50	300	8.50	10.1	19.6	8.7	57	--	20	20
46U323001	AT20x10-8	Fast Trekker	TL	3*	7	50	310	8.00	10.4	19.4	8.7	57	--	17	17
46U324	AT20x10-9	Fast Trekker	TL	3*	7	50	300	8.00	9.9	19.8	8.9	58	--	17	20
46U370001	AT20x7-8	Fast Trekker	TL	3*	7	50	240	5.50	7.4	20.3	9.2	60	--	14	16
46U3A1001	AT21x7-10	Fast Trekker	TL	3*	7	50	235	5.50	7.0	20.4	9.5	61	--	13	16
46U3B2001	AT21x8-9	Fast Trekker	TL	3*	7	50	240	6.50	7.4	20.2	9.2	60	--	13	16
46U3A5	AT22x11-10	Fast Trekker	TL	3*	7	50	385	9.00	11.0	22.0	9.9	64	--	21	16
46U387	AT22x11-8	Fast Trekker	TL	3*	7	50	395	9.00	11.0	21.3	9.6	63	--	21	16
46U3A8001	AT22x8-10	Fast Trekker	TL	3*	7	50	275	6.50	8.2	21.8	10	65	--	15	16

*See Approved Rim Contours section



MUD MONSTER



RAPTOR

Titan Mud Monster ATV

- In mud or extremely difficult terrain, the Titan Mud Monster offers maximum bite with a full 26" outside diameter
- A rounded profile maintains steer characteristics usually only associated with less aggressive designs

Titan Raptor ATV

- Just like its name implies, this tire is meant for the lost world
- Thick, talon-like lugs sink into gnarly terrain



Titan Sabre Tooth ATV

- If your idea of fun means pushing the envelope, then the Sabre Tooth is the tire for you
- The Sabre Tooth carries on the tradition of offering a general purpose tread design that gives outstanding performance

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
407306	AT25x8-12	Sabre Tooth	TL	3*	7	50	340	6.50	7.5	25.2	11.2	74	--	17	19
407321	AT25x10-12	Sabre Tooth	TL	3*	7	50	420	8.00	9.1	25.2	11.2	74	--	22	21
404336	AT26x10.5-12	Mud Monster	TL	3*	7	50	455	8.00	10.0	25.9	11.6	76	--	27	24
416336	AT26x10.5-12	Raptor	TL	3*	7	50	455	8.00	10.0	25.9	11.6	76	--	24	24

*See Approved Rim Contours section

Titan**ST**

ST RADIAL



ST II



ST



SPORT TRAX

Dico ST Radial

- Superb wet road traction, good highway stability and improved fuel economy
- Rated superb for wear performance

Dico ST Radial II

- Modern tread design for a smooth ride and more even wear
- Wider grooves and aggressive siping reduce hydroplaning
- Nylon cap improves durability

Titan ST

- Four-ply construction in tread and sidewall for improved tread wear and life
- Incorporates special tread compounds for extended mileage for a variety of trailer applications

Titan Sport Trax ST

- Designed for utility trailers on or off the highway
- Nylon construction for cooler running and rugged wear

Catalog #	Tire Size	Design	TL/TT	Load Rating	Inflation Pressure	Max Load mph	Max Load lbs	Design Rim Width*	Tire Width	Overall Diameter	Static Loaded Radius	Rolling Circ.	Flat Plate Area in ²	Weight	Tread Depth 32nd in.
463307	16.5x6.50-8	Sport Trax	TL	C	70	Highway	785	5.38	6.5	16.1	7.5	48	--	8	6
1106901-808	4.80-8	Sport Trax	TL	B	60	Highway	585	3.75	4.9	16.6	7.7	50	--	6	6
1107900-808	4.80-8	Sport Trax	TL	C	90	Highway	760	3.75	4.9	16.6	7.7	50	--	6	6
1114300-808	5.70-8	Sport Trax	TL	B	50	Highway	715	4.5	5.7	18.3	8.3	54	--	7	7
1115000-808	5.70-8	Sport Trax	TL	C	75	Highway	910	4.5	6	18.3	8.3	54	--	8	7
1136605	18.5x8.50-8	Sport Trax	TL	C	50	Highway	935	7	8.2	18.3	8.3	54	--	12	10
11099001	4.80-12	Sport Trax	TL	B	60	Highway	785	3.75	4.9	20.6	9.6	62	--	8	6
1139100	20.5x8.0-10	Sport Trax	TL	C	50	Highway	1,100	6	8.1	20.6	9.3	61	--	14	9
1139410	20.5x8.0-10	Sport Trax	TL	D	70	Highway	1,320	6	8.1	20.6	9.3	61	--	15	9
1139690	20.5x8.0-10	Sport Trax	TL	E	90	Highway	1,520	6	8.1	20.6	9.3	61	--	16	9
11127031	5.30-12	Sport Trax	TL	C	80	Highway	1,050	4.25	5.5	21.4	10.1	65	--	11	6
417366	6.90-9	ST	TL	A	60	Highway	1,100	5.5	7.6	21.5	9.9	64	--	16	10
6ST310	ST155/80R13	ST Radial	TL	C	50	Highway	1,100	4.5	5.8	23.1	10.6	69	--	15	11
6RT368	ST175/80R13	Radial ST II	TL	C	50	Highway	1,360	5	7.1	24	11.1	73	--	19	10
5ST367	ST175/80D13	ST	TL	B	35	Highway	1,100	4.5	6.8	24.3	11.2	73	--	15	10
5ST368	ST175/80D13	ST	TL	C	50	Highway	1,360	4.5	6.8	24.3	11.2	73	--	18	10
6RT320	ST185/80R13	Radial ST II	TL	C	50	Highway	1,480	5	7.3	24.7	11.3	75	--	20	10
5ST320	ST185/80D13	ST	TL	C	50	Highway	1,480	4.5	7.1	24.9	11.3	73	--	19	10
6RT357	ST205/75R14	Radial ST II	TL	C	50	Highway	1,760	5.5	8	26.1	12	79	--	22	10
6RT352	ST215/75R14	Radial ST II	TL	C	50	Highway	1,870	6	8.7	26.6	12.2	81	--	25	10
5ST357	ST205/75D14	ST	TL	C	50	Highway	1,760	5.5	8	26.9	12.1	79	--	22	10
6RT318	ST205/75R15	Radial ST II	TL	C	50	Highway	1,820	5.5	8	27.1	12.4	82	--	23	10
6RT319	ST205/75R15	Radial ST II	TL	D	65	Highway	2,150	5.5	8	27.1	12.4	82	--	28	10
5ST352	ST215/75D14	ST	TL	C	50	Highway	1,870	6	8.2	27.1	12.5	81	--	23	10
5ST318	ST205/75D15	ST	TL	C	50	Highway	1,820	5.5	8.1	28	12.5	81	--	26	11
5ST319	ST205/75D15	ST	TL	D	65	Highway	2,150	5.5	8.1	28	12.5	81	--	30	11
6RT346	ST225/75R15	Radial ST II	TL	C	50	Highway	2,150	6	8.8	28.5	13	86	--	28	10
6RT347	ST225/75R15	Radial ST II	TL	D	65	Highway	2,540	6	8.8	28.5	13	86	--	31	10