



DOMINANDO EL TERRITORIO



BIAS OFF THE ROAD TYRES



G2/L2

A



G2/L2

B

G2/L2 A

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube
		(mm)	(32nds)		Section Width (mm)	Overall Diameter (mm)	Single		Single		
							(kPa)	(psi)	(kg)	(Lbs)	
13.00-24	12	24.5	30.9	8.00	333	1278	450	65	5600	12300	TL
13.00-24	14	24.5	30.9	8.00	333	1278	525	76	6000	13200	TL
13.00-24	16	24.5	30.9	8.00	333	1278	600	87	6500	14300	TL
14.00-24	12	25.5	32.1	8.00	362	1348	425	62	6300	13900	TL
14.00-24	16	25.5	32.1	8.00	362	1348	550	80	7300	16100	TL

G2/L2 B

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube
		(mm)	(32nds)		Section Width (mm)	Overall Diameter (mm)	Single		Single		
							(kPa)	(psi)	(kg)	(Lbs)	
17.5-25	12	25	31.5	14.00/1.5	445	1348	200	29	2900	6400	TL
17.5-25	16	25	31.5	14.00/1.5	445	1348	275	40	3350	7400	TL
20.5-25	16	26.5	33.4	17.00/2.0	521	1493	225	33	4000	8800	TL
20.5-25	20	26.5	33.4	17.00/2.0	521	1493	275	40	4500	9900	TL



BIAS OFF THE ROAD TYRES



E3/L3

A



E3/L3

B



E3/L3

C

E3/L3 A

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube	
		(mm)	(32nds)		Section Width (mm)	Overall Diameter (mm)	Single		Single		TT	TL
17.5-25	12	25.5	32.1	14.00/1.5	445	1348	225	33	3650	8050	TT/TL	
17.5-25	16	25.5	32.1	14.00/1.5	445	1348	300	44	4250	9350	TT/TL	
20.5-25	16	29	36.5	17.00/2.0	521	1493	275	40	5450	12000	TT/TL	
20.5-25	20	29	36.5	17.00/2.0	521	1493	325	47	6000	13200	TT/TL	
23.5-25	16	32	40.3	19.50/2.5	597	1617	225	33	6150	13600	TT/TL	
23.5-25	20	32	40.3	19.50/2.5	597	1617	300	44	7300	16100	TT/TL	
26.5-25	28	35	44.1	22.00/3.0	673	1750	475	69	15500	34200	TT/TL	
29.5-25	28	36	45.4	25.00/3.5	749	1874	325	47	11500	25400	TT/TL	

E3/L3 B

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube	
		(mm)	(32nds)		Section Width (mm)	Overall Diameter (mm)	Single		Single		TT	TL
23.5-25	16	31.5	39.7	19.50/2.5	597	1617	225	33	6150	13600	TT/TL	
23.5-25	20	31.5	39.7	19.50/2.5	597	1617	300	44	7300	16100	TT/TL	

E3/L3 C

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube	
		(mm)	(32nds)		Section Width (mm)	Overall Diameter (mm)	Single		Single		TT	TL
14.00-24	24	25	31.5	10.00	375	1418	575	83	5150	11400	TT	



BIAS OFF THE ROAD TYRES



G3/L3



E3/L3

G3/L3

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube
					Section Width (mm)	Overall Diameter (mm)	Single		Single		
		(mm)	(32nds)				(kPa)	(psi)	(kg)	(Lbs)	TT
14.00-24TG	16	30	37.8	10.00VA	393	1338	350	50	3650	8030	TL

E3/L3

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube	
					Section Width (mm)	Overall Diameter (mm)	Dual/*Single		Dual/*Single			
		(mm)	(32nds)				(kPa)	(psi)	(kg)	(Lbs)	TT	TL
16.00-25	28	30	37.8	11.25	432	1493	575*750	83*109	6700*11500	14800*25400	TL	
16.00-25	32	30	37.8	11.25	432	1493	650*875	94*127	7300*12500	16095*27560	TL	
18.00-25	32	32	40.3	13.00	498	1617	575*750	83*109	8750*15000	19300*33100	TL	
18.00-25	40	32	40.3	13.00	498	1617	700*950	101*138	9700*21385	17000*37480	TL	



PORT USE TYRES



E4



E3/L3

E4

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube	
		(mm)	(32nds)		Section Width (mm)	Overall Diameter (mm)	Single		Single			
							(kPa)	(psi)	(kg)	(Lbs)	TT	TL
12.00-20	24	45	56.7	8.50	315	1146	1000	145	9800	21600	TT	

E3/L3

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube	
					Section Width (mm)	Overall Diameter (mm)	Single		Single			
		(mm)	(32nds)				(kPa)	(psi)	(kg)	(Lbs)	TT	TL
14.00-24	24	25	31.5	10.00	375	1418	575	83	5150	11400	TT	



MOBILE HOME TYRES



HWY

A



HWY

B



HWY

C

HWY A

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube
		(mm)	(32nds)		Section Width (mm)	Overall Diameter (mm)	Single		Single		
							(kPa)	(psi)	(kg)	(Lbs)	
8–14.5	14	6	7.6	6.00	194	680	790	115	1405	3100	TL
8–14.5	14	6	7.6	6.00	203	707	790	115	1405	3100	TL

HWY B

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube
		(mm)	(32nds)		Section Width (mm)	Overall Diameter (mm)	Single		Single		
							(kPa)	(psi)	(kg)	(Lbs)	TT
9-14.5	14	9	11.3	7.00	241	711	790	115	1590	3500	TL

HWY C

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube	
					Section Width (mm)	Overall Diameter (mm)	Single		Single			
		(mm)	(32nds)				(kPa)	(psi)	(kg)	(Lbs)	TT	TL
215/60D14.5	14	7	8.8	6.00	196	628	760	110	1405	3100		TL
235/60D14.5	14	8.6	10.8	7.00	230	673	760	110	1590	3500		TL



BIAS TRUCK TYRES



HWY

L



HWY

M



HWY

N

HWY L

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube	
		(mm)	(32nds)		Section Width (mm)	Overall Diameter (mm)	Dual/*Single		Dual/*Single		TT	TL
10.00-20	12	11.5	14.5	7.50	278	1054	520/*590	75/*85	2180/*2500	4805/*5510	TT	TL
10.00-20	14	11.5	14.5	7.50	278	1054	620/*690	90/*100	2430/*2800	5355/*6175	TT	TL

HWY M

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube	
		(mm)	(32nds)		Section Width (mm)	Overall Diameter (mm)	Dual/*Single		Dual/*Single			
							(kPa)	(psi)	(kg)	(Lbs)	TT	TL
7.50–17	10	10.5	13.2	6.00	215	859	550/*620	80/*90	1260/*1440	2780/*3170	TL	

HWY N (BUCKSHOT MUDDER)

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube	
					Section Width (mm)	Overall Diameter (mm)	Single		Single			
		(mm)	(32nds)				(kPa)	(psi)	(kg)	(Lbs)	TT	TL
N78-15LT	6	22	27.7	7.00	230	785	310	45	872	1920	TL	TL
P78-16LT	6	23	29.0	6.50	219	830	310	45	990	2180	TL	TL



SPECIAL TRAILER TYRES



HWY

G



HWY

H



HWY

I

HWY G

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube	
		(mm)	(32nds)		Section Width (mm)	Overall Diameter (mm)	Dual/*Single		Dual/*Single			
							(kPa)	(psi)	(kg)	(Lbs)	TT	TL
ST175/80D13	6	6.5	8.2	5.00	177	610	350/*350	50/*50	545/*615	1200/*1360	TL	
ST205/75D14	6	8	10.1	5.50	203	664	350/*350	50/*50	710/*800	1570/*1760	TL	
ST205/75D15	6	8	10.1	5.50	203	689	350/*350	50/*50	730/*825	1610/*1820	TL	
ST225/75D15	6	8	10.1	6.00	223	719	450/*450	65/*65	1000/*1150	2200/*2540	TL	

HWY H

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube	
		(mm)	(32nds)		Section Width (mm)	Overall Diameter (mm)	Single		Single			
							(kPa)	(psi)	(kg)	(Lbs)	TT	TL
20.5x8.0-10	4	7	8.8	6.00	203	518	240	35	412	910	TL	
20.5x8.0-10	6	7	8.8	6.00	203	518	340	50	501	1105	TL	
20.5x8.0-10	8	7	8.8	6.00	203	518	480	70	603	1330	TL	
20.5x8.0-10	10	7	8.8	6.00	203	518	620	90	696	1535	TL	
20.5x8.0-10	12	7	8.8	6.00	203	518	650	95	787	1735	TL	

HWY I

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube	
		(mm)	(32nds)		Section Width (mm)	Overall Diameter (mm)	Single		Single			
							(kPa)	(psi)	(kg)	(Lbs)	TT	TL
18.5x8.5-8	4	7	8.8	7.00	213	462	240	35	349	770	TL	
18.5x8.5-8	6	7	8.8	7.00	213	462	340	50	500	1100	TL	
20.5x8.0-10	4	7	8.8	6.00	203	518	240	35	412	910	TL	
20.5x8.0-10	6	7	8.8	6.00	203	518	340	50	501	1105	TL	
20.5x8.0-10	8	7	8.8	6.00	203	518	480	70	603	1330	TL	
20.5x8.0-10	10	7	8.8	6.00	203	518	620	90	696	1535	TL	
20.5x8.0-10	12	7	8.8	6.00	203	518	650	95	787	1735	TL	



SPECIAL TRAILER TYRES



HWY I



HWY J



HWY K

HWY I (GOLF TYRES)

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube
					Section Width (mm)	Overall Diameter (mm)	Single		Single		
		(mm)	(32nds)				(kPa)	(psi)	(kg)	(Lbs)	TT
18X8.5-8	4	6	7.60	7.00	213	445	150	22	370	815	TL

HWY J

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube	
					Section Width	Overall Diameter	Single		Single			
		(mm)	(32nds)		(mm)	(mm)	(kPa)	(psi)	(kg)	(Lbs)	TT	TL
4.80-8	4	5.5	6.9	3.75	121	423	410	60	267	590	TL	
4.80-8	6	5.5	6.9	3.75	121	423	620	90	345	760	TL	
5.70-8	4	6	7.6	4.50	146	469	340	50	325	715	TL	
5.70-8	6	6	7.6	4.50	146	469	520	75	412	910	TL	
5.70-8	8	6	7.6	4.50	146	469	690	100	487	1070	TL	
4.80-12	4	5.5	6.9	3.75	121	524	410	60	267	590	TL	
4.80-12	6	5.5	6.9	3.75	121	524	620	90	450	990	TL	
5.30-12	4	6	7.6	4.25	135	548	380	55	387	855	TL	
5.30-12	6	6	7.6	4.25	135	548	550	80	475	1050	TL	

HWY K

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube
					Section Width (mm)	Overall Diameter (mm)	Single		Single		
		(mm)	(32nds)				(kPa)	(psi)	(kg)	(Lbs)	
5.70-8	8	6	7.60	4.50	146	469	690	100	490	1075	TL



TRAILER TYRES



HWY

D



HWY

E



HWY

F

HWY D

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube
		(mm)	(32nds)		Section Width (mm)	Overall Diameter (mm)	Dual/*Single (kPa)	Dual/*Single (psi)	Dual/*Single (kg)	Dual/*Single (Lbs)	
7.00-15	8	9.5	12	5.50F	200	750	410/*410	60/*60	825/*925	1820/*2040	TL
7.50-16	10	9.5	12	6.00G	215	805	520/*520	75/*75	1120/*1250	2470/*2755	TL

HWY E

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube
		(mm)	(32nds)		Section Width (mm)	Overall Diameter (mm)	Dual/*Single (kPa)	Dual/*Single (psi)	Dual/*Single (kg)	Dual/*Single (Lbs)	
7.50-16	10	11	13.9	6.00G	215	805	520/*520	75/*75	1120/*1250	2470/*2755	TL

HWY F

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube
		(mm)	(32nds)		Section Width (mm)	Overall Diameter (mm)	Dual/*Single (kPa)	Dual/*Single (psi)	Dual/*Single (kg)	Dual/*Single (Lbs)	
10.00-20	12	11.5	14.5	7.5	278	1054	520/*590	75/*85	2180/*2500	4805/*5510	TT
10.00-20	14	11.5	14.5	7.5	278	1054	620/*690	90/*100	2430/*2800	5355/*6175	TT
10.00-20	16	11.5	14.5	7.5	278	1054	720/*790	105/*115	2650/*3000	5840/*6610	TT
11-22.5	12	11.5	14.5	8.25	279	1054	520/*590	75/*85	2180/*2500	4805/*5510	TL
11-22.5	14	11.5	14.5	8.25	279	1054	620/*690	90/*100	2430/*2800	5355/*6175	TL
11-22.5	16	11.5	14.5	8.25	279	1054	720/*790	105/*115	2650/*3000	5840/*6610	TL



TRAILER TYRES



HWY

D



HWY

O



HWY

P

HWY D

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube
		(mm)	(32nds)		Section Width (mm)	Overall Diameter (mm)	Dual/*Single (kPa)	(psi)	Dual/*Single (kg)	(Lbs)	
ST205/90D15	8	9.5	12.0	5J	200	750	450*450	65*65	1180/1030	2600/2270	TL
ST205/90D15	10	9.5	12.0	5J	200	750	550*550	80*80	1320/1150	2910/2540	TL
ST225/90D16	10	9.5	12.0	6J	215	805	520*520	75*75	1560/3440	1370/3020	TL

HWY O

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube
		(mm)	(32nds)		Section Width (mm)	Overall Diameter (mm)	Dual/*Single (kPa)	(psi)	Dual/*Single (kg)	(Lbs)	
ST205/90D15	8	11	13.9	5J	200	750	450*450	65*65	1180/1030	2600/2270	TL

HWY P

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube
		(mm)	(32nds)		Section Width (mm)	Overall Diameter (mm)	Single (kPa)	(psi)	Single (kg)	(Lbs)	
7-14.5ST	12	6	7.6	6.00	194	680	690	100	1059	2335	TL
8-14.5ST	14	6	7.6	6.00	203	707	790	115	1405	3100	TL



AGRICULTURE TYRES


F2

F2M

F3

L4

F2 (3 GUIAS)

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube	
		(mm)	(32nds)		Section Width (mm)	Overall Diameter (mm)	Single		Single		TT	TL
6.00-16SL	6	17	21.4	4.00	159	739	360	52	515	1135	TT	
7.50-16SL	8	20	25.2	5.50	203	808	385	56	775	1705	TT	

F2M (4 GUIAS)

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube	
		(mm)	(32nds)		Section Width (mm)	Overall Diameter (mm)	Single		Single		TT	TL
10.00-16SL	10	25	31.5	8.00	274	894	300	44	1120	2480	TT	

F3

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube	
		(mm)	(32nds)		Section Width (mm)	Overall Diameter (mm)	Single		Single		TT	TL
11L-16SL	12	11	13.9	8.00	279	838	440	64	1250	2760	TL	

L4

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube	
		(mm)	(32nds)		Section Width (mm)	Overall Diameter (mm)	Single		Single		TT	TL
11L-16SL	12	16	20.2	8.00	279	838	440	64	1250	2760	TL	



SKID STEER LOADER TYRES


SKS

L4

KL4

SKS

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube	
					Section Width	Overall Diameter	Single		Single			
		(mm)	(32nds)		(mm)	(mm)	(kPa)	(psi)	(kg)	(Lbs)	TT	TL
10–16.5	10	18	22.7	8.25	264	773	520	75	2135	4710	TL	
12–16.5	12	18	22.7	9.75	307	831	550	80	2865	6315	TL	
14–17.5	14	20	25.2	10.50	349	921	550	80	3875	8540	TL	
15–19.5	14	20	25.2	11.75	389	1019	485	70	4565	10060	TL	

L4

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube	
					Section Width (mm)	Overall Diameter (mm)	Single		Single			
		(mm)	(32nds)				(kPa)	(psi)	(kg)	(Lbs)	TT	TL
10-16.5	10	27.5	34.7	8.25	264	773	520	75	2135	4710		TL
12-16.5	12	31.5	39.7	9.75	307	831	550	80	2865	6315		TL

KL4

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube
		(mm)	(32nds)		Section Width (mm)	Overall Diameter (mm)	Single		Single		
							(kPa)	(psi)	(kg)	(Lbs)	
10–16.5	10	27	34.0	8.25	264	773	520	75	2135	4710	TL
12–16.5	12	35	44.1	9.75	307	831	550	80	2865	6315	TL
33*15.5–16.5	14	35	44.1	12.00	380	836	480	70	3150	6950	TL



AGRICULTURE TYRES


R1
A

R1
B

R1
C

R1
D

R1 A

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube
					Section Width	Overall Diameter	Single		Single		
		(mm)	(32nds)		(mm)	(mm)	(kPa)	(psi)	(kg)	(Lbs)	TT
12.4-24	8	36	45.4	11.00	315	1159	220	32	1285	2830	TT
13.6-24	8	36	45.4	12.00	345	1210	190	28	1400	3080	TT
14.9-24	8	36	45.4	11.00	378	1265	180	26	1600	3520	TT
14.9-28	8	36	45.4	13.00	378	1367	180	26	1700	3740	TT

R1 B

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube
					Section Width	Overall Diameter	Single		Single		
		(mm)	(32nds)		(mm)	(mm)	(kPa)	(psi)	(kg)	(Lbs)	
15.5-38	8	37.5	47.3	14.00	394	1569	180	26	1850	4075	TT
18.4-30	10	37.5	47.3	16.00	467	1552	180	26	2500	5510	TT
18.4-34	10	37.5	47.3	16.00	467	1654	180	26	2725	6005	TT
18.4-38	10	37.5	47.3	16.00	467	1802	180	26	2900	6400	TT

R1 C (IRRIGATION TYRES)

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube
					Section Width	Overall Diameter	Single		Single		
		(mm)	(32nds)		(mm)	(mm)	(kPa)	(psi)	(kg)	(Lbs)	
11.2-24	6	25	31.5	10.00	284	1103	180	26	950	2090	TT
11.2-38	6	25	31.5	10.00	284	1459	180	26	1150	2530	TT
14.9-24	6	25	31.5	13.00	378	1265	180	26	1600	3520	TT

R1 D

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube
		(mm)	(32nds)		Section Width (mm)	Overall Diameter (mm)	Single		Single		
							(kPa)	(psi)	(kg)	(Lbs)	
12-38	8	34	42.8	DW11	330	1575	140	20	1570	3460	TT

AGRICULTURE TYRES


R1

I1

I3

IMP
E

R1 E

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube
		(mm)	(32nds)		Section Width (mm)	Overall Diameter (mm)	Single (kPa)	Single (psi)	Single (kg)	Single (Lbs)	
16.9-30	8	37	46.6	15	429	1485	165	24	2000	4400	TT TL

I1

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube
		(mm)	(32nds)		Section Width (mm)	Overall Diameter (mm)	Single (kPa)	Single (psi)	Single (kg)	Single (Lbs)	
9.5L-15SL	12	7.5	9.5	7.00	241	767	440	64	1450	3200	TL
11L-15SL	12	7.5	9.5	8.00	279	777	360	52	1450	3200	TL

I3

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube
		(mm)	(32nds)		Section Width (mm)	Overall Diameter (mm)	Single (kPa)	Single (psi)	Single (kg)	Single (Lbs)	
10.0/75-15.3	8	25	31.5	9.00	264	760	310	44	950	2100	TL
11.5/80-15.3	8	25	31.5	9.00	290	845	270	39	1180	2600	TL

IMP

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube
		(mm)	(32nds)		Section Width (mm)	Overall Diameter (mm)	Single (kPa)	Single (psi)	Single (kg)	Single (Lbs)	
10.0/75-15.3	10	9	11.3	9.00	264	760	390	57	1550	3415	TL
10.0/75-15.3	12	9	11.3	9.00	264	760	470	68	1700	3745	TL
10.0/75-15.3	14	9	11.3	9.00	264	760	550	80	1900	4190	TL
11.5/80-15.3	10	10	12.6	9.00	290	845	340	49	1950	4295	TL
11.5/80-15.3	12	10	12.6	9.00	290	845	410	59	2180	4805	TL
11.5/80-15.3	14	10	12.6	9.00	290	845	475	69	2430	5355	TL
12.5/80-15.3	14	10.5	13.2	9.00	307	889	430	62	2650	5840	TL
12.5/80-15.3	16	10.5	13.2	9.00	307	889	490	71	2820	6215	TL

AGRICULTURE TYRES


R4
A

R4
B

R4
C

R4 A

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube
					Section Width (mm)	Overall Diameter (mm)	Single		Single		
		(mm)	(32nds)				(kPa)	(psi)	(kg)	(Lbs)	TT
19.5L-24	12	26	32.8	17.00	495	1339	230	34	3450	7600	TL

R4 B

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube
					Section Width (mm)	Overall Diameter (mm)	Single		Single		
		(mm)	(32nds)				(kPa)	(psi)	(kg)	(Lbs)	
17.5L-24	12	25	31.5	15.00	445	1241	190	28	1725	3800	TL
19.5L-24	12	26	32.8	17.00	495	1339	230	34	3450	7600	TL
21L-24	12	27	34.0	18.00	533	1378	220	32	3875	8550	TL

R4 C

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube
					Section Width (mm)	Overall Diameter (mm)	Single		Single		
		(mm)	(32nds)				(kPa)	(psi)	(kg)	(Lbs)	
19.5L-24	12	27.5	34.7	17.00	495	1339	230	34	3450	7600	TL



AGRICULTURE TYRES


R4
D

R4
E

R4
F

R4 D

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube	
		(mm)	(32nds)		Section Width (mm)	Overall Diameter (mm)	Single		Single		TT	TL
10.5/80-18	10	22	27.7	9.00	274	885	370	54	1950	4295	TL	
12.5/80-18	12	27	34.0	9.00	308	965	370	54	2650	5840	TL	

R4 E

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube	
		(mm)	(32nds)		Section Width (mm)	Overall Diameter (mm)	Single		Single		TT	TL
12.5/80-18	12	25	31.5	9.00	308	965	370	54	2650	5840	TL	

R4 F

Size	P.R.	Tread Depth		Rim	New tire inflated dimensions		Pressure		Max. Load		Tube	
		(mm)	(32nds)		Section Width (mm)	Overall Diameter (mm)	Single		Single		TT	TL
16.9-24	12	27	34.0	15.00	429	1309	260	37	3250	7150	TL	
16.9-28	12	33	41.6	15.00	429	1427	260	37	3550	7850	TL	
18.4-26	12	28	35.3	16.00	467	1426	220	32	2650	5840	TL	
18.4-28	12	39	49.1	16.00	467	1500	250	36	4000	8800	TL	





DISTRIBUIDOR AUTORIZADO



**DOMINANDO
EL TERRITORIO**